
SikaProof® A+ 08

DECLARATION OF PERFORMANCE

No. 33691495

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	33691495
2	INTENDED USE/S	EN 13967:2012 Plastic and rubber sheets intended for use as damp proofing in buildings
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 2+ for type testing System 3 for reaction to fire
6a	HARMONISED STANDARD:	EN 13967:2012
	Notified body/ies:	1213

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Reaction to fire	Class E	System 3	
Watertightness	Pass	System 2+	
Tear resistance:			
Machine direction	≥ 200 N	System 2+	
Cross direction	≥ 200 N		
Joint strength	≥ 100N/50 mm	System 2+	
Impact resistance	≥ 300 mm	System 2+	
Tensile properties:			
Tensile strength:			
Machine direction	≥ 500 N/50mm	System 2+	
Cross direction	≥ 500 N/50mm		EN 13967:2012
Elongation:			
Machine direction	≥ 1000 %	System 2+	
Cross direction	≥ 1000 %		
Resistance to static loading	≥ 20 kg	System 2+	
Durability:			
Watertightness after artificial ageing	Pass	System 2+	
Watertightness after exposure to chemicals	Pass		
Dangerous substances	NPD	System 2+	

**8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR -
SPECIFIC TECHNICAL DOCUMENTATION**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Tomasz Gutowski
Function: Corporate Standardization
and Approvals
At Warsaw on 18 May 2020

Name : Tatiana Ageyeva
Function: Standardization and Approvals
At Warsaw on 18 May 2020



.....

.....

End of information as required by Regulation (EU) No 305/2011



20

Sika Services AG, Zurich, Switzerland

33691495

EN 13967:2012

Notified Body 1213

Plastic and rubber sheets intended for use as damp proofing in buildings

Reaction to fire	Class E
Watertightness	Pass
Tear resistance:	
Machine direction	≥ 200 N
Cross direction	≥ 200 N
Joint strength	≥ 100 N/50 mm
Impact resistance	≥ 300 mm
Tensile properties:	
Tensile strength:	
Machine direction	≥ 500 N/50mm
Cross direction	≥ 500 N/50mm
Elongation:	
Machine direction	≥ 1000 %
Cross direction	≥ 1000 %
Resistance to static loading	≥ 20 kg
Durability:	
Watertightness after artificial ageing	Pass
Watertightness after exposure to chemicals	Pass

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

Declaration of Performance

SikaProof® A+ 08
33691495
2020.05 , ver. 2
1005, 1193

Template for translation. Only for
internal use

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

SikaProof® A+ 08
33691495
2020.05 , ver. 2
1005, 1193

5/6

Template for translation. Only for
internal use

BUILDING TRUST



Sika Services AG
Tüffenwies 16-22
8064 Zürich
Switzerland
www.sika.com

Declaration of Performance
SikaProof® A+ 08
33691495
2020.05 , ver. 2
1005, 1193

6/6

Template for translation. Only for
internal use

BUILDING TRUST

