

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sika® Poxicolor® Part B



Revision Date: 14.04.2021
Date of last issue: -

Version 1.0

Print Date 15.04.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sika® Poxicolor® Part B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Corrosion protection, For professional users only.

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Deutschland GmbH
Kornwestheimer Str. 103-107
D-70439 Stuttgart
Telephone : +49 711 8009 0
E-mail address of person : EHS@de.sika.com
responsible for the SDS

1.4 Emergency telephone number

Emergency CONTACT (24-Hour-Number):
GBK GmbH Global Regulatory Compliance +49(0)6132-84463

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

| | |
|--|---|
| Flammable liquids, Category 3 | H226: Flammable liquid and vapour. |
| Acute toxicity, Category 4 | H302: Harmful if swallowed. |
| Acute toxicity, Category 4 | H332: Harmful if inhaled. |
| Skin corrosion, Sub-category 1B | H314: Causes severe skin burns and eye damage. |
| Serious eye damage, Category 1 | H318: Causes serious eye damage. |
| Skin sensitisation, Category 1 | H317: May cause an allergic skin reaction. |
| Specific target organ toxicity - single exposure, Category 3, Respiratory system | H335: May cause respiratory irritation. |
| Specific target organ toxicity - repeated exposure, Category 2 | H373: May cause damage to organs through prolonged or repeated exposure if inhaled. |
| Long-term (chronic) aquatic hazard, Category 2 | H411: Toxic to aquatic life with long lasting effects. |

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sika® Poxicolor® Part B



Revision Date: 14.04.2021
Date of last issue: -

Version 1.0

Print Date 15.04.2021

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word :

Danger

Hazard statements :

H226 Flammable liquid and vapour.
H302 + H332 Harmful if swallowed or if inhaled.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.
H373 May cause damage to organs through prolonged or repeated exposure if inhaled.
H411 Toxic to aquatic life with long lasting effects.

Supplemental Hazard Statements :

EUH071 Corrosive to the respiratory tract.

Precautionary statements :

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P391 Collect spillage.

Hazardous components which must be listed on the label:

xylene
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxirane, reaction products with ethylenediamine

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sika® Poxicolor® Part B



Revision Date: 14.04.2021

Version 1.0

Print Date 15.04.2021

Date of last issue: -

m-phenylenebis(methylamine)
3-aminomethyl-3,5,5-trimethylcyclohexylamine

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: This substance/mixture contains components considered to have endocrine disrupting properties for environment, according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

| Chemical name | CAS-No. EC-No. Registration number | Classification | Concentration (% w/w) |
|--|--|--|--------------------------|
| xylene Contains: ethylbenzene <= 25 % | 1330-20-7 215-535-7 01-2119488216-32-XXXX | Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 3; H412 | >= 25 - < 40 |
| benzyl alcohol | 100-51-6 202-859-9 01-2119492630-38-XXXX | Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Irrit. 2; H319 | >= 10 - < 20 |
| Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxirane, reaction products with ethylenediamine Contains: ethylenediamine <= 1 % | 72480-18-3 500-253-1 01-2120766318-46-XXXX | Acute Tox. 4; H302 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 | >= 10 - < 20 |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sika® Poxicolor® Part B



Revision Date: 14.04.2021

Version 1.0

Print Date 15.04.2021

Date of last issue: -

| | | | |
|--|---|---|--------------|
| m-phenylenebis(methylamine) | 1477-55-0 216-032-5 01-2119480150-50-XXXX | Acute Tox. 4; H302 Acute Tox. 4; H332 Skin Corr. 1B; H314 Skin Sens. 1; H317 Aquatic Chronic 3; H412 EUH071 | >= 5 - < 10 |
| 3-aminomethyl-3,5,5-trimethylcyclohexylamine | 2855-13-2 220-666-8 01-2119514687-32-XXXX | Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Corr. 1B; H314 Skin Sens. 1A; H317 Aquatic Chronic 3; H412 Eye Dam. 1; H318 | >= 5 - < 10 |
| butan-1-ol | 71-36-3 200-751-6 01-2119484630-38-XXXX | Flam. Liq. 3; H226 Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) | >= 3 - < 5 |
| 4-tert-butylphenol | 98-54-4 202-679-0 01-2119489419-21-XXXX | Skin Irrit. 2; H315 Eye Dam. 1; H318 Repr. 2; H361f Aquatic Chronic 1; H410 M-Factor (Chronic aquatic toxicity): 1 | >= 1 - < 2,5 |

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficul-



- ty.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Keep eye wide open while rinsing.
- If swallowed : Do not induce vomiting without medical advice.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Gastrointestinal discomfort
Cough
Respiratory disorder
Allergic reactions
Headache
Dermatitis
See Section 11 for more detailed information on health effects and symptoms.
- Risks : Health injuries may be delayed.
corrosive effects
irritant effects
sensitising effects
- Harmful if swallowed or if inhaled.
May cause an allergic skin reaction.
Causes serious eye damage.
May cause respiratory irritation.
May cause damage to organs through prolonged or repeated exposure if inhaled.
Corrosive to the respiratory tract.
Causes severe burns.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.
-

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

- Unsuitable extinguishing : Water
-



media High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.
Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Use water spray to cool unopened containers.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Remove all sources of ignition.
Deny access to unprotected persons.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.



SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).
 Do not get in eyes, on skin, or on clothing.
 For personal protection see section 8.
 Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
 Smoking, eating and drinking should be prohibited in the application area.
 Take precautionary measures against static discharge.
 Provide sufficient air exchange and/or exhaust in work rooms.
 Open drum carefully as content may be under pressure.
 Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
 Follow standard hygiene measures when handling chemical products
- Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully re-sealed and kept upright to prevent leakage. Store in accordance with local regulations.
- Storage class (TRGS 510) : 3, Flammable liquids
- Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form of exposure) | Control parameters * | Basis * |
|------------|---------|-------------------------------|----------------------|---------|
|------------|---------|-------------------------------|----------------------|---------|

SAFETY DATA SHEET
 according to Regulation (EC) No. 1907/2006
Sika® Poxicolor® Part B



Revision Date: 14.04.2021
 Date of last issue: -

Version 1.0

Print Date 15.04.2021

| | | | | |
|---|-----------|---------------------------|-----------------------|-------------|
| xylene | 1330-20-7 | TWA | 50 ppm 221 mg/m3 | 2000/39/EC |
| Further information: Identifies the possibility of significant uptake through the skin, Indicative | | | | |
| | | STEL | 100 ppm 442 mg/m3 | 2000/39/EC |
| | | AGW | 100 ppm 440 mg/m3 | DE TRGS 900 |
| Peak-limit: excursion factor (category): 2;(II) | | | | |
| Further information: Skin absorption | | | | |
| benzyl alcohol | 100-51-6 | AGW (Vapour and aerosols) | 5 ppm 22 mg/m3 | DE TRGS 900 |
| Peak-limit: excursion factor (category): 2;(I) | | | | |
| Further information: Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission)., Sum of vapor and aerosols., Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child | | | | |
| butan-1-ol | 71-36-3 | AGW | 100 ppm 310 mg/m3 | DE TRGS 900 |
| Peak-limit: excursion factor (category): 1;(I) | | | | |
| Further information: Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission)., When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child | | | | |
| 4-tert-butylphenol | 98-54-4 | AGW (Vapour and aerosols) | 0,08 ppm 0,5 mg/m3 | DE TRGS 900 |
| Peak-limit: excursion factor (category): 2;(II) | | | | |
| Further information: Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission)., Sum of vapor and aerosols., Skin absorption | | | | |

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

Biological occupational exposure limits

| Substance name | CAS-No. | Control parameters | Sampling time | Basis |
|--------------------|-----------|--|---|----------|
| xylene | 1330-20-7 | xylene: 1,5 mg/l (Blood) | Immediately after exposure or after working hours | TRGS 903 |
| | | methylhippuric acid (all isomers): 2 g/l (Urine) | Immediately after exposure or after working hours | TRGS 903 |
| butan-1-ol | 71-36-3 | 1-butanol: 2 mg/g Creatinine (Urine) | Before next shift | TRGS 903 |
| | | 1-butanol: 10 mg/g Creatinine (Urine) | Immediately after exposure or after working hours | TRGS 903 |
| 4-tert-butylphenol | 98-54-4 | 4-tert-butylphenol (p-tert-butylphenol): 2 mg/l | Immediately after exposure or after working hours | TRGS 903 |



| | | | |
|--|--|---------|--|
| | | (Urine) | |
|--|--|---------|--|

8.2 Exposure controls

Personal protective equipment

- Eye protection : Safety glasses with side-shields conforming to EN166
Eye wash bottle with pure water
Wear eye/face protection.
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
- Suitable for short time use or protection against splashes:
Butyl rubber/nitrile rubber gloves (> 0,1 mm)
Contaminated gloves should be removed.
Suitable for permanent exposure:
Viton gloves (0.4 mm),
breakthrough time >30 min.
- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
- Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
organic vapor (Type A) and particulate filter
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm
P1: Inert material; P2, P3: hazardous substances
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.
Ensure adequate ventilation, especially in confined areas.

Environmental exposure controls

- General advice : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Physical state : liquid

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sika® Poxicolor® Part B



Revision Date: 14.04.2021
Date of last issue: -

Version 1.0

Print Date 15.04.2021

| | | |
|--|---|--|
| Colour | : | various |
| Odour | : | amine-like |
| Odour Threshold | : | No data available |
| pH | : | Not applicable substance/mixture is non-soluble (in water) |
| Melting point/range / Freezing point | : | No data available |
| Boiling point/boiling range | : | No data available |
| Flash point | : | ca. 30 °C Method: closed cup |
| Evaporation rate | : | No data available |
| Flammability (solid, gas) | : | No data available |
| Upper explosion limit / Upper flammability limit | : | 7 %(V) |
| Lower explosion limit / Lower flammability limit | : | 1 %(V) |
| Vapour pressure | : | 7,9993 hPa |
| Relative vapour density | : | No data available |
| Density | : | 0,97 g/cm ³ (20 °C) |
| Solubility(ies) | : | |
| Water solubility | : | insoluble |
| Solubility in other solvents | : | No data available |
| Partition coefficient: n-octanol/water | : | No data available |
| Auto-ignition temperature | : | 355 °C |
| Decomposition temperature | : | No data available |
| Viscosity | : | |
| Viscosity, dynamic | : | No data available |
| Viscosity, kinematic | : | > 20,5 mm ² /s (40 °C) |
| Explosive properties | : | No data available |

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sika® Poxicolor® Part B



Revision Date: 14.04.2021
Date of last issue: -

Version 1.0

Print Date 15.04.2021

Oxidizing properties : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.
Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if swallowed or if inhaled.

Components:

xylene:

Acute oral toxicity : LD50 Oral (Rat): 3.523 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 1.700 mg/kg

benzyl alcohol:

Acute oral toxicity : LD50 Oral (Rat): 1.620 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 4,178 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sika® Poxicolor® Part B



Revision Date: 14.04.2021
Date of last issue: -

Version 1.0

Print Date 15.04.2021

m-phenylenebis(methylamine):

- Acute oral toxicity : LD50 Oral (Rat): 930 mg/kg
- Acute inhalation toxicity : LC50 (Rat): 1,34 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: Corrosive to the respiratory tract.
- Acute dermal toxicity : LD50 Dermal (Rat): > 3.100 mg/kg

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

- Acute oral toxicity : LD50 Oral (Rat): 1.030 mg/kg
- Acute inhalation toxicity : LC50 (Rat): > 5,01 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
- Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg

butan-1-ol:

- Acute oral toxicity : LD50 Oral (Rat): ca. 2.000 mg/kg
- Acute dermal toxicity : LD50 Dermal (Rabbit): 3.430 mg/kg

Skin corrosion/irritation

Causes severe burns.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause respiratory irritation.
Corrosive to the respiratory tract.

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sika® Poxicolor® Part B



Revision Date: 14.04.2021
Date of last issue: -

Version 1.0

Print Date 15.04.2021

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure if inhaled.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

xylene:

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 2,2 mg/l
Exposure time: 73 h
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC: > 1,3 mg/l
Exposure time: 56 d
Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 1,17 mg/l
Exposure time: 7 d
Species: Daphnia (water flea)

benzyl alcohol:

Toxicity to fish : LC50 (Fish): > 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h

m-phenylenebis(methylamine):

Toxicity to fish : LC50 (Oryzias latipes (Japanese medaka)): > 10 - 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l
Exposure time: 48 h



3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): > 10 - 100 mg/l
Exposure time: 72 h

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment : This substance/mixture contains components considered to have endocrine disrupting properties for environment , according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : In accordance with the EWC Waste Regulation the classification of waste is to be assigned to the jurisdiction of the origin of waste. Therefore, it is not possible to assign a particular waste identification number.
Completely emptied packagings may be given for recycling.
Empty packaging may still contain hazardous residues. Empty packaging should be removed by a licensed waste contractor.
Sika has agreed disposal contracts for all packaging which is

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sika® Poxicolor® Part B



Revision Date: 14.04.2021
Date of last issue: -

Version 1.0

Print Date 15.04.2021

brought into circulation in Germany.
For further details see www.sika.de

SECTION 14: Transport information

14.1 UN number

ADR : UN 2924
IMDG : UN 2924
IATA : UN 2924

14.2 UN proper shipping name

ADR : FLAMMABLE LIQUID, CORROSIVE, N.O.S.
(xylene, m-phenylenebis(methylamine))
IMDG : FLAMMABLE LIQUID, CORROSIVE, N.O.S.
(xylene, m-phenylenebis(methylamine), Aliphatic amine ad-
duct)
IATA : Flammable liquid, corrosive, n.o.s.
(xylene, m-phenylenebis(methylamine))

14.3 Transport hazard class(es)

ADR : 3
IMDG : 3
IATA : 3

14.4 Packing group

ADR
Packing group : II
Classification Code : FC
Hazard Identification Number : 338
Labels : 3 (8)
Tunnel restriction code : (D/E)
IMDG
Packing group : II
Labels : 3 (8)
EmS Code : F-E, S-C
Remarks : Alkalis

IATA (Cargo)

Packing instruction (cargo aircraft) : 363
Packing instruction (LQ) : Y340
Packing group : II
Labels : Flammable Liquids, Corrosive

IATA (Passenger)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sika® Poxicolor® Part B



Revision Date: 14.04.2021

Version 1.0

Print Date 15.04.2021

Date of last issue: -

Packing instruction (passenger aircraft) : 352
Packing instruction (LQ) : Y340
Packing group : II
Labels : Flammable Liquids, Corrosive

14.5 Environmental hazards

ADR

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

IATA (Passenger)

Environmentally hazardous : yes

IATA (Cargo)

Environmentally hazardous : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet.

Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 3

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : 4-tert-butylphenol ethylenediamine

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sika® Poxicolor® Part B



Revision Date: 14.04.2021

Version 1.0

Print Date 15.04.2021

Date of last issue: -

of dangerous chemicals

REACH Information: All substances contained in our Products are
- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

E2 ENVIRONMENTAL HAZARDS

P5c FLAMMABLE LIQUIDS

Water contaminating class : WGK 2 obviously hazardous to water
(Germany) Classification according to AwSV, Annex 1 (5.2)

Volatile organic compounds : Law on the incentive tax for volatile organic compounds
(VOCV)
Volatile organic compounds (VOC) content: 50,82 %

Directive 2010/75/EU of 24 November 2010 on industrial
emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 50,82 %

GISCODE : RE70

Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Product is no subject to the Chemicals Prohibition Ordinance.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H226 : Flammable liquid and vapour.
H302 : Harmful if swallowed.
H304 : May be fatal if swallowed and enters airways.
H312 : Harmful in contact with skin.
H314 : Causes severe skin burns and eye damage.
H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sika® Poxicolor® Part B



Revision Date: 14.04.2021

Version 1.0

Print Date 15.04.2021

Date of last issue: -

| | | |
|-------|---|---|
| H332 | : | Harmful if inhaled. |
| H335 | : | May cause respiratory irritation. |
| H336 | : | May cause drowsiness or dizziness. |
| H361f | : | Suspected of damaging fertility. |
| H373 | : | May cause damage to organs through prolonged or repeated exposure if inhaled. |
| H400 | : | Very toxic to aquatic life. |
| H410 | : | Very toxic to aquatic life with long lasting effects. |
| H412 | : | Harmful to aquatic life with long lasting effects. |

Full text of other abbreviations

| | | |
|-------------------|---|--|
| Acute Tox. | : | Acute toxicity |
| Aquatic Acute | : | Short-term (acute) aquatic hazard |
| Aquatic Chronic | : | Long-term (chronic) aquatic hazard |
| Asp. Tox. | : | Aspiration hazard |
| Eye Dam. | : | Serious eye damage |
| Eye Irrit. | : | Eye irritation |
| Flam. Liq. | : | Flammable liquids |
| Repr. | : | Reproductive toxicity |
| Skin Corr. | : | Skin corrosion |
| Skin Irrit. | : | Skin irritation |
| Skin Sens. | : | Skin sensitisation |
| STOT RE | : | Specific target organ toxicity - repeated exposure |
| STOT SE | : | Specific target organ toxicity - single exposure |
| 2000/39/EC | : | Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values |
| DE TRGS 900 | : | Germany. TRGS 900 - Occupational exposure limit values. |
| TRGS 903 | : | TRGS 903 - Biological limit values |
| 2000/39/EC / TWA | : | Limit Value - eight hours |
| 2000/39/EC / STEL | : | Short term exposure limit |
| DE TRGS 900 / AGW | : | Time Weighted Average |
| ADR | : | European Agreement concerning the International Carriage of Dangerous Goods by Road |
| CAS | : | Chemical Abstracts Service |
| DNEL | : | Derived no-effect level |
| EC50 | : | Half maximal effective concentration |
| GHS | : | Globally Harmonized System |
| IATA | : | International Air Transport Association |
| IMDG | : | International Maritime Code for Dangerous Goods |
| LD50 | : | Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals) |
| LC50 | : | Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period) |
| MARPOL | : | International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978 |
| OEL | : | Occupational Exposure Limit |
| PBT | : | Persistent, bioaccumulative and toxic |
| PNEC | : | Predicted no effect concentration |
| REACH | : | Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency |

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006

Sika® Poxicolor® Part B



Revision Date: 14.04.2021
Date of last issue: -

Version 1.0

Print Date 15.04.2021

SVHC : Substances of Very High Concern
vPvB : Very persistent and very bioaccumulative

Further information

Classification of the mixture:

| | |
|-------------------|------|
| Flam. Liq. 3 | H226 |
| Acute Tox. 4 | H302 |
| Acute Tox. 4 | H332 |
| Skin Corr. 1B | H314 |
| Eye Dam. 1 | H318 |
| Skin Sens. 1 | H317 |
| STOT SE 3 | H335 |
| STOT RE 2 | H373 |
| Aquatic Chronic 2 | H411 |

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.



Changes as compared to previous version !

DE / EN