according to Regulation (EC) No. 1907/2006

# SikaCor®-146 DW Part B

Revision Date: 06.07.2021 Version 5.0 Print Date 06.07.2021

Date of last issue: 23.01.2019

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : SikaCor®-146 DW Part B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Special coating, For professional users only.

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Deutschland GmbH

Kornwestheimer Str. 103-107

D-70439 Stuttgart +49 711 8009 0

Telephone : E-mail address of person :

responsible for the SDS

EHS@de.sika.com

1.4 Emergency telephone number

Emergency CONTACT (24-Hour-Number):

GBK GmbH Global Regulatory Compliance +49(0)6132-84463

### **SECTION 2: Hazards identification**

# 2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin corrosion, Sub-category 1A H314: Causes severe skin burns and eye damage.

Serious eye damage, Category 1 H318: Causes serious eye damage.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

#### 2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word : Danger

Hazard statements : H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

Supplemental Hazard : EUH071 Corrosive to the respiratory tract.

Statements

Country DE 100000003965

according to Regulation (EC) No. 1907/2006

# SikaCor®-146 DW Part B

Precautionary statements

Revision Date: 06.07.2021 Version 5.0 Print Date 06.07.2021

Date of last issue: 23.01.2019

Sika®

Prevention:

P261 Avoid breathing mist or vapours.

P280 Wear protective gloves/ protective clothing/

eye protection/ face protection.

Response:

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do

NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immedi-

ately all contaminated clothing. Rinse skin

with water.

P304 + P340 + P310 IF INHALED: Remove person to fresh

air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously

with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER/ doctor.

#### Hazardous components which must be listed on the label:

Cashew (Anacardium occidentale) Nutshell Extract, decarboxylated, Distilled m-phenylenebis(methylamine) trimethylhexane-1,6-diamine

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# **SECTION 3: Composition/information on ingredients**


#### 3.2 Mixtures

Components

Oomponenta			
Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Registration number		
Cashew (Anacardium occidentale)	8007-24-7	Acute Tox. 4; H302	>= 10 - < 20
Nutshell Extract, decarboxylated,	700-991-6	Acute Tox. 4; H312	
Distilled	01-2119502450-57-	Skin Irrit. 2; H315	
	XXXX	Eye Dam. 1; H318	
		Skin Sens. 1A; H317	

according to Regulation (EC) No. 1907/2006

# SikaCor®-146 DW Part B



Date of last issue: 23.01.2019

m-phenylenebis(methylamine)	1477-55-0 216-032-5 01-2119480150-50- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H332 Skin Corr. 1B; H314 Skin Sens. 1; H317 Aquatic Chronic 3; H412 EUH071	>= 10 - < 20
trimethylhexane-1,6-diamine	25620-58-0 247-134-8 01-2119560598-25- XXXX (belongs to CAS 25513-64-8)	Acute Tox. 4; H302 Skin Corr. 1A; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Chronic 3; H412	>= 5 - < 10

For explanation of abbreviations see section 16.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water.

Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficul-

tv.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

#### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Allergic reactions

Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

according to Regulation (EC) No. 1907/2006

# SikaCor®-146 DW Part B

Revision Date: 06.07.2021 Version 5.0 Print Date 06.07.2021

Date of last issue: 23.01.2019

Risks : Health injuries may be delayed.

> corrosive effects sensitising effects

May cause an allergic skin reaction. Causes serious eye damage. Corrosive to the respiratory tract.

Causes severe burns.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

# **SECTION 5: Firefighting measures**

### 5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon diox-

ide/sand/foam/alcohol resistant foam/chemical powder for

extinction.

#### 5.2 Special hazards arising from the substance or mixture

ucts

Hazardous combustion prod- : No hazardous combustion products are known

#### 5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information Standard procedure for chemical fires.

#### **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment.

Deny access to unprotected persons.

### 6.2 Environmental precautions

Do not flush into surface water or sanitary sewer system. **Environmental precautions** 

If the product contaminates rivers and lakes or drains inform

respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

according to Regulation (EC) No. 1907/2006

# SikaCor®-146 DW Part B

Revision Date: 06.07.2021 Version 5.0 Print Date 06.07.2021

Date of last issue: 23.01.2019

#### 6.4 Reference to other sections

For personal protection see section 8.

# **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage

areas and containers

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accord-

ance with local regulations.

Storage class (TRGS 510) : 8A, Combustible, corrosive hazardous materials

Further information on stor-

age stability

No decomposition if stored and applied as directed.

#### 7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any

use.

# **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

Contains no substances with occupational exposure limit values.

according to Regulation (EC) No. 1907/2006

# SikaCor®-146 DW Part B

Revision Date: 06.07.2021 Version 5.0 Print Date 06.07.2021

Date of last issue: 23.01.2019

### 8.2 Exposure controls

#### **Engineering measures**

Maintain air concentrations below occupational exposure standards.

Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

Wear eye/face protection.

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

organic vapor (Type A) and particulate filter

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm P1: Inert material; P2, P3: hazardous substances

Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

#### **Environmental exposure controls**

General advice : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

#### **SECTION 9: Physical and chemical properties**

# 9.1 Information on basic physical and chemical properties

Country DE 100000003965

6 / 14

according to Regulation (EC) No. 1907/2006

# SikaCor®-146 DW Part B

Revision Date: 06.07.2021 Version 5.0 Print Date 06.07.2021

Date of last issue: 23.01.2019

Physical state : liquid (20 °C) Colour : dark brown

Odour : amine-like

Boiling point/boiling range : 201 °C

Flash point : > 101 °C

Method: closed cup

Auto-ignition temperature : No data available

pH : 10 - 11 (25 °C)

**Viscosity** 

Viscosity, dynamic : 760 mPa.s (25 °C)

Viscosity, kinematic : > 20,5 mm2/s (40 °C)

Solubility(ies)

Water solubility : immiscible

Solubility in other solvents : insoluble

Vapour pressure : 0,01 hPa

Density : ca. 1 g/cm3 (20 °C)

# 9.2 Other information

No data available

# **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

#### 10.2 Chemical stability

The product is chemically stable.

# 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

according to Regulation (EC) No. 1907/2006

# SikaCor®-146 DW Part B

Revision Date: 06.07.2021 Version 5.0 Print Date 06.07.2021

Date of last issue: 23.01.2019

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

#### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

### **SECTION 11: Toxicological information**

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

### **Acute toxicity**

Not classified based on available information.

#### Components:

#### Cashew (Anacardium occidentale) Nutshell Extract, decarboxylated, Distilled:

Acute oral toxicity : LD50 Oral (Rat): > 2.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rat): 2.000 mg/kg

m-phenylenebis(methylamine):

Acute oral toxicity : LD50 Oral (Rat): 930 mg/kg

Acute inhalation toxicity : LC50 (Rat): 1,34 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: Corrosive to the respiratory tract.

Acute dermal toxicity : LD50 Dermal (Rat): > 3.100 mg/kg

#### Skin corrosion/irritation

Causes severe burns.

# Serious eye damage/eye irritation

Causes serious eye damage.

#### Respiratory or skin sensitisation

#### Skin sensitisation

May cause an allergic skin reaction.

### Respiratory sensitisation

Not classified based on available information.

#### Germ cell mutagenicity

Not classified based on available information.

according to Regulation (EC) No. 1907/2006

# SikaCor®-146 DW Part B

Revision Date: 06.07.2021 Version 5.0 Print Date 06.07.2021

Date of last issue: 23.01.2019

#### Carcinogenicity

Not classified based on available information.

#### Reproductive toxicity

Not classified based on available information.

#### STOT - single exposure

Corrosive to the respiratory tract.

#### STOT - repeated exposure

Not classified based on available information.

#### **Aspiration toxicity**

Not classified based on available information.

#### 11.2 Information on other hazards

# **Endocrine disrupting properties**

#### **Product:**

Assessment The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

#### **SECTION 12: Ecological information**

# 12.1 Toxicity

#### **Components:**

#### m-phenylenebis(methylamine):

Toxicity to fish : LC50 (Oryzias latipes (Japanese medaka)): > 10 - 100 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l

Exposure time: 48 h

# 12.2 Persistence and degradability

No data available

#### 12.3 Bioaccumulative potential

No data available

#### 12.4 Mobility in soil

No data available


### 12.5 Results of PBT and vPvB assessment

#### **Product:**

Assessment : This substance/mixture contains no components considered

according to Regulation (EC) No. 1907/2006

# SikaCor®-146 DW Part B



to be either p

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

### 12.6 Endocrine disrupting properties

#### **Product:**

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

#### 12.7 Other adverse effects

#### **Product:**

Additional ecological infor-

mation

: There is no data available for this product.

# **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : In accordance with the EWC Waste Regulation the classifica-

tion of waste is to be assigned to the jurisdiction of the origin of waste. Therefore, it is not possible to assign a particular

waste identification number.

Completely emptied packagings may be given for recycling. Empty packaging may still contain hazardous residues. Empty packaging should be removed by a licensed waste contractor. Sika has agreed disposal contracts for all packaging which is

brought into circulation in Germany. For further details see www.sika.de

#### **SECTION 14: Transport information**

### 14.1 UN number

ADR : UN 2735 IMDG : UN 2735 IATA : UN 2735

14.2 UN proper shipping name

ADR : AMINES, LIQUID, CORROSIVE, N.O.S.

(trimethylhexane-1,6-diamine, m-phenylenebis(methylamine))

IMDG : AMINES, LIQUID, CORROSIVE, N.O.S.

(trimethylhexane-1,6-diamine, m-phenylenebis(methylamine))

according to Regulation (EC) No. 1907/2006

# SikaCor®-146 DW Part B

Revision Date: 06.07.2021 Version 5.0 Print Date 06.07.2021

Date of last issue: 23.01.2019

**IATA** : Amines, liquid, corrosive, n.o.s.

(trimethylhexane-1,6-diamine, m-phenylenebis(methylamine))

14.3 Transport hazard class(es)

 ADR
 : 8

 IMDG
 : 8

 IATA
 : 8

#### 14.4 Packing group

**ADR** 

Packing group : III
Classification Code : C7
Hazard Identification Number : 80
Labels : 8
Tunnel restriction code : (E)

**IMDG** 

Packing group : III
Labels : 8
EmS Code : F-A, S-B

IATA (Cargo)

Packing instruction (cargo : 856

aircraft)

Packing instruction (LQ) : Y841
Packing group : III

Labels : Corrosive

IATA (Passenger)

Packing instruction (passen: 852

ger aircraft)

Packing instruction (LQ) : Y841
Packing group : III

Labels : Corrosive

#### 14.5 Environmental hazards

**ADR** 

Environmentally hazardous : no

**IMDG** 

Marine pollutant : no

IATA (Passenger)

Environmentally hazardous : no

IATA (Cargo)

Environmentally hazardous : no

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

Print Date 06.07.20

according to Regulation (EC) No. 1907/2006

# SikaCor®-146 DW Part B

Date of last issue: 23.01.2019

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

# **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

Conditions of restriction for the following entries should be considered:

Number on list 3

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

Not applicable

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

None of the components are listed

(=> 0.1 %).

REACH - List of substances subject to authorisation

(Annex XIV)

Not applicable

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

Not applicable

REACH Information: All substances contained in our Products are

- registered by our upstream suppliers, and/or

- registered by us, and/or

excluded from the regulation, and/orexempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Water hazard class (Germa-

WGK 2 obviously hazardous to water

ny)

Classification according to AwSV, Annex 1 (5.2)

Volatile organic compounds : Law on the incentive tax for volatile organic compounds

(VOCV) no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)

Country DE 100000003965

12 / 14

according to Regulation (EC) No. 1907/2006

# SikaCor®-146 DW Part B

Revision Date: 06.07.2021 Version 5.0 Print Date 06.07.2021

Date of last issue: 23.01.2019



Not applicable

#### Other regulations:

Product is no subject to the Chemicals Prohibition Ordinance.

### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

#### **SECTION 16: Other information**

#### **Full text of H-Statements**

H302 : Harmful if swallowed. H312 : Harmful in contact with skin.

H314 : Causes severe skin burns and eye damage.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.

H332 : Harmful if inhaled.

H412 : Harmful to aquatic life with long lasting effects.

#### Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Dam. : Serious eye damage
Skin Corr. : Skin corrosion
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

according to Regulation (EC) No. 1907/2006

# SikaCor®-146 DW Part B

Date of last issue: 23.01.2019

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

#### **Further information**

#### Classification of the mixture: Classification procedure:

Skin Corr. 1A H314 Calculation method Eye Dam. 1 H318 Calculation method Skin Sens. 1 H317 Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

DE / EN