

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## SikaCor® Elastomastic TF (Sika® Elastomastic TF) Part B



Revision Date: 21.04.2021

Version 5.0

Print Date 21.04.2021

Date of last issue: 05.08.2020

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : SikaCor® Elastomastic TF (Sika® Elastomastic TF) Part B

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Corrosion protection, For professional users only.

#### 1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Deutschland GmbH  
Kornwestheimer Str. 103-107  
D-70439 Stuttgart  
Telephone : +49 711 8009 0  
E-mail address of person : EHS@de.sika.com  
responsible for the SDS

#### 1.4 Emergency telephone number

Emergency CONTACT (24-Hour-Number):  
GBK GmbH Global Regulatory Compliance +49(0)6132-84463

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Skin corrosion, Sub-category 1B	H314: Causes severe skin burns and eye damage.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through prolonged or repeated exposure if swallowed.
Short-term (acute) aquatic hazard, Category 1	H400: Very toxic to aquatic life.
Long-term (chronic) aquatic hazard, Category 2	H411: Toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## SikaCor® Elastomastic TF (Sika® Elastomastic TF) Part B



Revision Date: 21.04.2021

Version 5.0

Print Date 21.04.2021

Date of last issue: 05.08.2020

Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H373 May cause damage to organs through prolonged or repeated exposure if swallowed. H410 Very toxic to aquatic life with long lasting effects.
Precautionary statements	:	<b>Prevention:</b> P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. <b>Response:</b> P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor. P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor. P391 Collect spillage.

### Hazardous components which must be listed on the label:

Phenol, methylstyrenated  
3-aminomethyl-3,5,5-trimethylcyclohexylamine  
(Z)-N-9-octadecenylpropane-1,3-diamine  
m-phenylenebis(methylamine)

### Additional Labelling

||| EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## SikaCor® Elastomastic TF (Sika® Elastomastic TF) Part B



Revision Date: 21.04.2021

Version 5.0

Print Date 21.04.2021

Date of last issue: 05.08.2020

Ecological information: This substance/mixture contains components considered to have endocrine disrupting properties for environment, according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

##### Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
Phenol, methylstyrenated	Not Assigned 700-960-7 270-966-8 01-2119555274-38-XXXX	Skin Irrit. 2; H315 Skin Sens. 1; H317 Aquatic Chronic 3; H412	>= 25 - < 40
3-aminomethyl-3,5,5-trimethylcyclohexylamine	2855-13-2 220-666-8 01-2119514687-32-XXXX	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Corr. 1B; H314 Skin Sens. 1A; H317 Aquatic Chronic 3; H412 Eye Dam. 1; H318	>= 5 - < 10
2,4,6-tris(dimethylaminomethyl)phenol Contains: bis[(dimethylamino)methyl]phenol <= 15 %	90-72-2 202-013-9 01-2119560597-27-XXXX	Acute Tox. 4; H302 Skin Corr. 1C; H314 Eye Dam. 1; H318	>= 3 - < 5
(Z)-N-9-octadecenylpropane-1,3-diamine	7173-62-8 230-528-9 01-2119487002-46-XXXX	Acute Tox. 4; H302 Skin Corr. 1B; H314 STOT RE 1; H372 Aquatic Acute 1; H400 Aquatic Chronic 1; H410  M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 1	>= 1 - < 2,5
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7 236-675-5 01-2119489379-17-XXXX	Carc. 2; H351	>= 1 - < 2,5

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## SikaCor® Elastomastic TF (Sika® Elastomastic TF) Part B



Revision Date: 21.04.2021

Version 5.0

Print Date 21.04.2021

Date of last issue: 05.08.2020

m-phenylenebis(methylamine)	1477-55-0 216-032-5 01-2119480150-50-XXXX	Acute Tox. 4; H302 Acute Tox. 4; H332 Skin Corr. 1B; H314 Skin Sens. 1; H317 Aquatic Chronic 3; H412 EUH071	>= 1 - < 2,5
4-nonylphenol, branched	84852-15-3 284-325-5 01-2119510715-45-XXXX	Repr. 2; H361fd Acute Tox. 4; H302 Skin Corr. 1B; H314 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 <u>Eye Dam. 1; H318</u>  M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 10	>= 1 - < 2,5

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.  
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
Continue rinsing eyes during transport to hospital.  
Remove contact lenses.  
Keep eye wide open while rinsing.
- If swallowed : Do not induce vomiting without medical advice.  
Rinse mouth with water.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## SikaCor® Elastomastic TF (Sika® Elastomastic TF) Part B



Revision Date: 21.04.2021

Version 5.0

Print Date 21.04.2021

Date of last issue: 05.08.2020

Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.

### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Allergic reactions  
Dermatitis  
See Section 11 for more detailed information on health effects and symptoms.
- Risks : Health injuries may be delayed.  
corrosive effects  
sensitising effects
- May cause an allergic skin reaction.  
Causes serious eye damage.  
May cause damage to organs through prolonged or repeated exposure if swallowed.  
Causes severe burns.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for extinction.

### 5.2 Special hazards arising from the substance or mixture

- Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : No hazardous combustion products are known

### 5.3 Advice for firefighters

- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## SikaCor® Elastomastic TF (Sika® Elastomastic TF) Part B



Revision Date: 21.04.2021

Version 5.0

Print Date 21.04.2021

Date of last issue: 05.08.2020

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Deny access to unprotected persons.

#### 6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.  
If the product contaminates rivers and lakes or drains inform respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For personal protection see section 8.

---

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Smoking, eating and drinking should be prohibited in the application area.  
Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Store in accordance with local regulations.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## SikaCor® Elastomastic TF (Sika® Elastomastic TF) Part B



Revision Date: 21.04.2021

Version 5.0

Print Date 21.04.2021

Date of last issue: 05.08.2020

Storage class (TRGS 510) : 8A, Combustible, corrosive hazardous materials

Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters *	Basis *
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ]	13463-67-7	AGW (Inhalable fraction)	10 mg/m <sup>3</sup> (Titanium dioxide)	DE TRGS 900
Peak-limit: excursion factor (category): 2;(II)				
		AGW (Alveolate fraction)	1,25 mg/m <sup>3</sup> (Titanium dioxide)	DE TRGS 900
Peak-limit: excursion factor (category): 2;(II)				

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

### 8.2 Exposure controls

#### Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166  
Eye wash bottle with pure water  
Wear eye/face protection.

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.

Suitable for short time use or protection against splashes:  
Butyl rubber/nitrile rubber gloves (> 0,1 mm)  
Contaminated gloves should be removed.  
Suitable for permanent exposure:  
Viton gloves (0.4 mm),  
breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.

Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## SikaCor® Elastomastic TF (Sika® Elastomastic TF) Part B



Revision Date: 21.04.2021

Version 5.0

Print Date 21.04.2021

Date of last issue: 05.08.2020

organic vapor filter (Type A)  
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm  
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

### Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system.  
If the product contaminates rivers and lakes or drains inform respective authorities.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state	:	liquid
Appearance	:	paste
Colour	:	various
Odour	:	amine-like
Odour Threshold	:	No data available
pH	:	Not applicable substance/mixture is non-soluble (in water)
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flash point	:	> 101 °C Method: closed cup
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	0,02 hPa
Relative vapour density	:	No data available



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## SikaCor® Elastomastic TF (Sika® Elastomastic TF) Part B



Revision Date: 21.04.2021

Version 5.0

Print Date 21.04.2021

Date of last issue: 05.08.2020

---

Density : ca. 1,45 g/cm<sup>3</sup> (20 °C)

### Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : Not applicable

Decomposition temperature : No data available

### Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : > 20,5 mm<sup>2</sup>/s (40 °C)

Explosive properties : No data available

Oxidizing properties : No data available

## 9.2 Other information

No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

### 10.4 Conditions to avoid

Conditions to avoid : No data available

### 10.5 Incompatible materials

Materials to avoid : No data available

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## SikaCor® Elastomastic TF (Sika® Elastomastic TF) Part B



Revision Date: 21.04.2021

Version 5.0

Print Date 21.04.2021

Date of last issue: 05.08.2020

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Acute toxicity

Not classified based on available information.

##### Components:

##### **3-aminomethyl-3,5,5-trimethylcyclohexylamine:**

Acute oral toxicity : LD50 Oral (Rat): 1.030 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5,01 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg

##### **2,4,6-tris(dimethylaminomethyl)phenol:**

Acute oral toxicity : LD50 (Rat): > 1.999 mg/kg  
Remarks: Harmful if swallowed.  
Annex VI - Harmonised  
REGULATION (EC) No 1272/2008

##### **(Z)-N-9-octadecenylpropane-1,3-diamine:**

Acute oral toxicity : LD50 Oral (Rat): > 300 - 2.000 mg/kg

##### **m-phenylenebis(methylamine):**

Acute oral toxicity : LD50 Oral (Rat): 930 mg/kg

Acute inhalation toxicity : LC50 (Rat): 1,34 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: Corrosive to the respiratory tract.

Acute dermal toxicity : LD50 Dermal (Rat): > 3.100 mg/kg

##### **4-nonylphenol, branched:**

Acute oral toxicity : LD50 Oral (Rat): 1.412 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 3.160 mg/kg

##### **Skin corrosion/irritation**

Causes severe burns.

##### Components:

##### **2,4,6-tris(dimethylaminomethyl)phenol:**

Species : Rabbit

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## SikaCor® Elastomastic TF (Sika® Elastomastic TF) Part B



Revision Date: 21.04.2021

Version 5.0

Print Date 21.04.2021

Date of last issue: 05.08.2020

Assessment : Corrosive  
Method : OECD Test Guideline 404

Assessment : irritating  
Remarks : Annex VI - Harmonised  
REGULATION (EC) No 1272/2008

### Serious eye damage/eye irritation

Causes serious eye damage.

#### Components:

##### **2,4,6-tris(dimethylaminomethyl)phenol:**

Species : Rabbit  
Assessment : Causes serious eye damage.

Assessment : irritating  
Remarks : Annex VI - Harmonised  
REGULATION (EC) No 1272/2008

### Respiratory or skin sensitisation

#### **Skin sensitisation**

May cause an allergic skin reaction.

#### **Respiratory sensitisation**

Not classified based on available information.

#### **Germ cell mutagenicity**

Not classified based on available information.

#### **Carcinogenicity**

Not classified based on available information.

#### **Reproductive toxicity**

Not classified based on available information.

#### **STOT - single exposure**

Not classified based on available information.

#### **STOT - repeated exposure**

May cause damage to organs through prolonged or repeated exposure if swallowed.

#### **Aspiration toxicity**

Not classified based on available information.

## 11.2 Information on other hazards

### **Endocrine disrupting properties**

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## SikaCor® Elastomastic TF (Sika® Elastomastic TF) Part B



Revision Date: 21.04.2021

Version 5.0

Print Date 21.04.2021

Date of last issue: 05.08.2020

levels of 0.1% or higher.

---

### SECTION 12: Ecological information

#### 12.1 Toxicity

##### Components:

##### **3-aminomethyl-3,5,5-trimethylcyclohexylamine:**

Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): > 10 - 100 mg/l  
Exposure time: 72 h

##### **2,4,6-tris(dimethylaminomethyl)phenol:**

Toxicity to algae/aquatic plants : EC50 (Scenedesmus capricornutum (fresh water algae)): > 10 - 100 mg/l  
Exposure time: 72 h

##### **(Z)-N-9-octadecenylpropane-1,3-diamine:**

Toxicity to fish : LC50 (Fish): > 0,1 - 1 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 0,1 - 1 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): > 0,1 - 1 mg/l  
Exposure time: 72 h

M-Factor (Acute aquatic toxicity) : 10

M-Factor (Chronic aquatic toxicity) : 1

##### **m-phenylenebis(methylamine):**

Toxicity to fish : LC50 (Oryzias latipes (Japanese medaka)): > 10 - 100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l  
Exposure time: 48 h

##### **4-nonylphenol, branched:**

M-Factor (Acute aquatic toxicity) : 10

M-Factor (Chronic aquatic toxicity) : 10

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## SikaCor® Elastomastic TF (Sika® Elastomastic TF) Part B



Revision Date: 21.04.2021

Version 5.0

Print Date 21.04.2021

Date of last issue: 05.08.2020

---

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

### 12.6 Endocrine disrupting properties

#### Product:

Assessment : This substance/mixture contains components considered to have endocrine disrupting properties for environment , according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

### 12.7 Other adverse effects

#### Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Very toxic to aquatic life with long lasting effects.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : In accordance with the EWC Waste Regulation the classification of waste is to be assigned to the jurisdiction of the origin of waste. Therefore, it is not possible to assign a particular waste identification number.  
Completely emptied packagings may be given for recycling.  
Empty packaging may still contain hazardous residues. Empty packaging should be removed by a licensed waste contractor.  
Sika has agreed disposal contracts for all packaging which is brought into circulation in Germany.  
For further details see [www.sika.de](http://www.sika.de)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## SikaCor® Elastomastic TF (Sika® Elastomastic TF) Part B



Revision Date: 21.04.2021

Version 5.0

Print Date 21.04.2021

Date of last issue: 05.08.2020

### SECTION 14: Transport information

#### 14.1 UN number

**ADR** : UN 1760  
**IMDG** : UN 1760  
**IATA** : UN 1760

#### 14.2 UN proper shipping name

**ADR** : CORROSIVE LIQUID, N.O.S.  
(3-aminomethyl-3,5,5-trimethylcyclohexylamine, m-phenylenebis(methylamine), (Z)-N-9-octadecenylpropane-1,3-diamine)  
**IMDG** : CORROSIVE LIQUID, N.O.S.  
(3-aminomethyl-3,5,5-trimethylcyclohexylamine, m-phenylenebis(methylamine), (Z)-N-9-octadecenylpropane-1,3-diamine)  
**IATA** : Corrosive liquid, n.o.s.  
(3-aminomethyl-3,5,5-trimethylcyclohexylamine, m-phenylenebis(methylamine), (Z)-N-9-octadecenylpropane-1,3-diamine)

#### 14.3 Transport hazard class(es)

**ADR** : 8  
**IMDG** : 8  
**IATA** : 8

#### 14.4 Packing group

**ADR**  
Packing group : III  
Classification Code : C9  
Hazard Identification Number : 80  
Labels : 8  
Tunnel restriction code : (E)  
**IMDG**  
Packing group : III  
Labels : 8  
EmS Code : F-A, S-B  
Remarks : Alkalis  
**IATA (Cargo)**  
Packing instruction (cargo aircraft) : 856  
Packing instruction (LQ) : Y841  
Packing group : III  
Labels : Corrosive  
**IATA (Passenger)**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## SikaCor® Elastomastic TF (Sika® Elastomastic TF) Part B



Revision Date: 21.04.2021

Version 5.0

Print Date 21.04.2021

Date of last issue: 05.08.2020

Packing instruction (passenger aircraft) : 852  
Packing instruction (LQ) : Y841  
Packing group : III  
Labels : Corrosive

### 14.5 Environmental hazards

#### ADR

Environmentally hazardous : yes

#### IMDG

Marine pollutant : yes

#### IATA (Passenger)

Environmentally hazardous : yes

#### IATA (Cargo)

Environmentally hazardous : yes

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet.

Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:  
Number on list 3

4-nonylphenol, branched (Number on list 46a)

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : 4-nonylphenol, branched

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants : Not applicable

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## SikaCor® Elastomastic TF (Sika® Elastomastic TF) Part B



Revision Date: 21.04.2021

Version 5.0

Print Date 21.04.2021

Date of last issue: 05.08.2020

tants (recast)

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : 4-nonylphenol, branched

REACH Information: All substances contained in our Products are  
- registered by our upstream suppliers, and/or  
- registered by us, and/or  
- excluded from the regulation, and/or  
- exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

E1 ENVIRONMENTAL HAZARDS

Water contaminating class : WGK 3 highly hazardous to water  
(Germany) Classification according to AwSV, Annex 1 (5.2)

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)  
Volatile organic compounds (VOC) content: 0,88 %  
no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 0,88 %

### Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Product is no subject to the Chemicals Prohibition Ordinance.

## 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

## SECTION 16: Other information

### Full text of H-Statements

H302 : Harmful if swallowed.  
H312 : Harmful in contact with skin.  
H314 : Causes severe skin burns and eye damage.  
H315 : Causes skin irritation.  
H317 : May cause an allergic skin reaction.  
H318 : Causes serious eye damage.  
H332 : Harmful if inhaled.  
H351 : Suspected of causing cancer if inhaled.  
H361fd : Suspected of damaging fertility. Suspected of damaging the



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## SikaCor® Elastomastic TF (Sika® Elastomastic TF) Part B



Revision Date: 21.04.2021

Version 5.0

Print Date 21.04.2021

Date of last issue: 05.08.2020

- H372 : unborn child.  
: Causes damage to organs through prolonged or repeated exposure if swallowed.  
H400 : Very toxic to aquatic life.  
H410 : Very toxic to aquatic life with long lasting effects.  
H412 : Harmful to aquatic life with long lasting effects.

### Full text of other abbreviations

- Acute Tox. : Acute toxicity  
Aquatic Acute : Short-term (acute) aquatic hazard  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Carc. : Carcinogenicity  
Eye Dam. : Serious eye damage  
Repr. : Reproductive toxicity  
Skin Corr. : Skin corrosion  
Skin Irrit. : Skin irritation  
Skin Sens. : Skin sensitisation  
STOT RE : Specific target organ toxicity - repeated exposure  
DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.  
DE TRGS 900 / AGW : Time Weighted Average  
ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road  
CAS : Chemical Abstracts Service  
DNEL : Derived no-effect level  
EC50 : Half maximal effective concentration  
GHS : Globally Harmonized System  
IATA : International Air Transport Association  
IMDG : International Maritime Code for Dangerous Goods  
LD50 : Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)  
LC50 : Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)  
MARPOL : International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978  
OEL : Occupational Exposure Limit  
PBT : Persistent, bioaccumulative and toxic  
PNEC : Predicted no effect concentration  
REACH : Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency  
SVHC : Substances of Very High Concern  
vPvB : Very persistent and very bioaccumulative

### Further information

#### Classification of the mixture:

- Skin Corr. 1B H314  
Eye Dam. 1 H318  
Skin Sens. 1 H317

#### Classification procedure:

- Calculation method  
Calculation method  
Calculation method

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## SikaCor® Elastomastic TF (Sika® Elastomastic TF) Part B



Revision Date: 21.04.2021

Version 5.0

Print Date 21.04.2021

Date of last issue: 05.08.2020

---

STOT RE 2	H373	Calculation method
Aquatic Acute 1	H400	Calculation method
Aquatic Chronic 2	H411	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

|| Changes as compared to previous version !

DE / EN