

## PRODUCT DATA SHEET

# Gravel Guard Vario Fix

Adjustable gravel guard for gullies

## DESCRIPTION

Gravel Guard Vario Fix is a moulded part used as an attachment for gullies.

## USES

Gravel Guard Vario Fix serves as protection against gravel and leaves being washed into the gully. For diameters from D 50 mm (DN 50) to D 160 mm (DN 150).

## FEATURES

- Cold impact resistant
- Weather resistant
- UV-stabilised



## PRODUCT INFORMATION

<b>Composition</b>	Polyethylene (PE)	
<b>Packaging</b>	10 pieces in a box	
<b>Shelf life</b>	The product retains its properties when stored correctly	
<b>Storage conditions</b>	The products must be stored in original, unopened and undamaged sealed packaging in dry conditions at temperatures between +5 °C and + 30 °C. Always refer to packaging.	
<b>Dimensions</b>	Basket diameter	262 mm
	Basket height	77,5 mm

## SYSTEM INFORMATION

<b>System</b>	Suitable for: Sarnafil® and Sikaplan® gullies DN 50 to DN 150
---------------	--

## BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## ECOLOGY, HEALTH AND SAFETY

### REGULATION (EC) NO 1907/2006 - REACH

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

## APPLICATION INSTRUCTIONS

### APPLICATION

The unit is supplied ready for installation. Place the gravel basket in the centre of the gully, press the locking button down and turn to the right to lock.

For later removal, simply turn the button back to the left to unlock and pull out.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

**Sika Deutschland CH AG & Co KG**

Roofing

Kornwestheimer Strasse 103-107

70439 Stuttgart

Tel.: +49 711 8009-0

roofing@de.sika.com

www.sika.de/dachabdichtung

**PRODUCT DATA SHEET**

Gravel Guard Vario Fix

June 2025, Version 02.01

02094505145000049

GravelGuardVarioFix-en-DE-(06-2025)-2-1.pdf