

Substrate Preparation

Substrate (for example)	Mastic asphalt screed acc. to DIN EN 13813 (AS)	Cement based screed acc. to DIN EN 13813 (CT)	Calciumsulfate- or calciumsulfate flowing screed acc. to DIN EN 13813(CA/CAF)	Dry screed
Primer (for example)	SCHÖNOX® SHP (not necessary if sufficient sanding)	SCHÖNOX® VD		
Self levelling compound (for example)	SCHÖNOX® HS 10 SCHÖNOX® HS 10 F SCHÖNOX® HS 50			SCHÖNOX® HS 10

Floor Covering Installation

Covering/ Collection	Adhesive	Tool/ trowel acc. TKB	Approx. consumption g/m ²	Remark
Designcovering (LVT)	Range of application			
Needlefelt*	SCHÖNOX® EMICLASSIC® Universal pressure sensitive dispersion adhesive	TKB B1	approx. 350 g/m ²	
	SCHÖNOX® MULTI FLOOR Very low emission, multi-purpose dispersion adhesive	TKB B1	approx. 400 g/m ²	
	SCHÖNOX® TEX XTREME Textile covering dispersion adhesive	TKB B1	approx. 400 g/m ²	
	SCHÖNOX® COMBILEIT® Conductive universal adhesive for all conductive coverings	notched trowel, coarse	approx. 500 g/m ²	

* When installing conductive flooring coverings, please use the conductive universal dispersion adhesive SCHÖNOX COMBILEIT

All adhesive fulfill EC1^{PLUS} acc. to GEV requirements, unless otherwise noted.

Please follow the technical information of relevant SCHÖNOX product data sheets, the advices of the manufactures of floor covering and also according to the well-known guidelines and instructions. If in doubt please do some practical tests or call the SCHÖNOX Productservice under phone +492547/910-325. More detailed information, product data sheets or laying instructions are available under www.schoenox.com or www.filzfabrik-fulda.de