

Substrate Preparation

Substrate (for example)	Mastic asphalt screed acc. to DIN EN 13813 (AS)	Cement based screed acc. to DIN EN 13813 (CT)	Calciumsulfate- or calciumsulfate flowing screed acc. to DIN EN 13813(CA/CAF)	Dry screed
Primer (for example)	SCHÖNOX® SHP (not necessary if sufficient sanding)	SCHÖNOX® VD		
Self levelling compound (for example)	SCHÖNOX® HS 10 SCHÖNOX® HS 10 F SCHÖNOX® HS 50			SCHÖNOX® HS 10

Floor Covering Installation

Covering/ Collection	Adhesive	Tool/ trowel acc. TKB	Approx. consumption g/m ²	Remark
Designcovering (LVT)				Range of application
Allura wood Allura stone Allura abstract	SCHÖNOX® DUROCOLL Fibre reinforced, strong dispersion adhesive	TKB A1/A2	approx. 250 - 300 g/m ²	
	SCHÖNOX® PU 900 Solvent-free 2-component polyurethane adhesive	TKB A1	approx. 400 g/m ²	increased heat exposure (for e.g. shop windows, conservatories); wet load
Linoleum				
Decibel (polyolefin foam backing) Bulletin Board	SCHÖNOX® EMICLASSIC® Universal pressure sensitive dispersion adhesive	TKB A1/A2	approx. 300 - 350 g/m ²	
Ohmex (conductive)	SCHÖNOX® COMBILEIT® Conductive universal adhesive for all conductive coverings	notched trowel, coarse	approx. 500 g/m ²	
Artoleum, Marmoleum, Walton, Acoustic, Furniture, Corklinoleum	SCHÖNOX® LINO XTREME Linoleum dispersion adhesive	TKB B1	approx. 400 g/m ²	
Linoleum modular				
Modular Impressa	SCHÖNOX® PROTECT Universal adhesive for highest loads	TKB B1	approx. 430 g/m ²	
	SCHÖNOX® LINO XTREME Linoleum dispersion adhesive	TKB B1	approx. 400 g/m ²	

Floor Covering Installation

Covering/ Collection	Adhesive	Tool/ trowel acc. TKB	Approx. consumption g/m ²	Remark
PVC / CV/ PU				Range of application
Homogeneous vinyl: Allura ceramic Heterogeneous vinyl: Eternal, Smaragd, effect, Surstep (safety flooring), Safestep (safety flooring) CV: Novilon, Novilux	SCHÖNOX® EMICLASSIC® Universal pressure sensitive dispersion adhesive	TKB A1/A2	approx. 250 - 300 g/m ²	
Homogeneous vinyl: Colorex SD (<106 Ohm), Colorex EC (>106 Ohm)	SCHÖNOX® COMBILEIT® Conductive universal adhesive for all conductive coverings	notched trowel, coarse	approx. 300 g/m ²	
Homogeneous pvc				
Sphera	SCHÖNOX® EMICLASSIC® Universal pressure sensitive dispersion adhesive	TKB A1/A2	approx. 250 - 300 g/m ²	
	SCHÖNOX® DUROCOLL Fibre reinforced, strong dispersion adhesive	TKB A1/A2	approx. 250 - 300 g/m ²	
Textile				
Flotex: sheets, tiles Coral: Coral FR	SCHÖNOX® EMICLASSIC® Universal pressure sensitive dispersion adhesive	TKB B1	approx. 350 g/m ²	
Needlefelt Forte Forte Graphik Markant Markant Graphic Akzent	SCHÖNOX® DUROCOLL Fibre reinforced, strong dispersion adhesive	TKB B1	approx. 400 g/m ²	
	SCHÖNOX® TEX XTREME Textile covering dispersion adhesive	TKB B1	approx. 400 g/m ²	
Coral EV	SCHÖNOX® PU 900 Solvent-free 2-component polyurethane adhesive	TKB B1	approx. 700 g/m ²	
Tessera Westbond	SCHÖNOX® MULTIFIX Acrylic Adhesive and Tackifier	TKB A2	approx. 250 g/m ²	
	SCHÖNOX® TACKIFIER Very low emission anti slip fixation	roller	approx. 100 g/m ²	

All adhesive fullfill EC1^{PLUS} acc. to GEV requirements, unless otherwise noted.

Please follow the technical information of relevant SCHÖNOX product data sheets, the advices of the manufactures of floor covering and also according to the well-known guidelines and instructions. If in doubt please do some practical tests or call the SCHÖNOX Productservice under phone +02547/910-325. More detailed information, product data sheets or laying instructions are available under www.schoenox.com or www.forbo.com.