

Substrate Preparation

Substrates	Cavity floor FLOOR and more® G 30 (2-fold indented joint)	Cavity floor FLOOR and more® G 34 (2-fold indented joint)	Cavity floor FLOOR and more® G 40 (3-fold indented joint)
Primer (for example)	SCHÖNOX® VD (mixed 1:1 with water)		
Levelling compound (for example)	SCHÖNOX® HS 10 SCHÖNOX® HS 10 F SCHÖNOX® HS 50		

Floor Covering Installation

Covering	Adhesive	Tool/ trowel acc. TKB	approx. consumption/m ²	Remark
Textile, CV, linoleum and PVC coverings				
	SCHÖNOX® EMICLASSIC® Universal pressure sensitive dispersion adhesive	A1 - A4 B1 - B3	approx. 200 - 280 g/m ² approx. 350 - 450 g/m ²	
	SCHÖNOX® MULTI FLOOR Very low emission, multi-purpose dispersion adhesive	A1 - A2 B1 - B2	approx. 300 - 350 g/m ² approx. 370 - 500 g/m ²	
	SCHÖNOX® DUROCOLL Fibre reinforced, strong dispersion adhesive	A1 - A2 B1 - B2	approx. 250 - 300 g/m ² approx. 350 - 450 g/m ²	
Rubber coverings				
	SCHÖNOX® EMICLASSIC® Universal pressure sensitive dispersion adhesive	TKB A1/A2	approx. 250 - 300 g/m ²	

**Before laying parquet, no prior priming and filling is required if the cavity floor is laid properly.
The cavity floor FLOOR and more® G 30 is not approved for parquet installation!**

Block parquet				Installation only on FLOOR and more® G 40
	SCHÖNOX® iLINE® 400 Universal wood adhesive for all kind of wood	SCHÖNOX iLINE APP	approx. 900 g/m ²	*
	SCHÖNOX® PARKETT 600 Waterless universal SMP adhesive with hard glue-line for parquet	B11 - B15	approx. 1000 -1300 g/m ²	Consider notes!
	SCHÖNOX® PARKETT 400 Universal wood adhesive for all kind of wood	B11 - B15	approx. 1000 -1200 g/m ²	*

Floor Covering Installation

Covering	Adhesive	Tool / trowel acc. TKB	approx. consumption/m ²	Remark
Mosaic parquet				Installation only on FLOOR and more® G 40
	SCHÖNOX® iLINE® 400 Universal wood adhesive for all kind of wood	SCHÖNOX iLINE APP	approx. 900 g/m ²	*
	SCHÖNOX® PARKETT 600 Waterless universal SMP adhesive with hard glue-line for parquet	B6	approx. 800 g/m ²	*
	SCHÖNOX® PARKETT 400 Universal wood adhesive for all kind of wood	B6	approx. 800 g/m ²	*
Wood paving RE Wood type oak				Installation only on FLOOR and more® G 40
	SCHÖNOX® PARKETT 600 Waterless universal SMP adhesive with hard glue-line for parquet	B6 - B11	approx. 800 - 1000 g/m ²	* Obtain information about decoupling
Edgewise lamella				Installation only on FLOOR and more® G 40
	SCHÖNOX® iLINE® 400 Universal wood adhesive for all kind of wood	SCHÖNOX iLINE APP	approx. 900 g/m ²	*
	SCHÖNOX® PARKETT 600 Waterless universal SMP adhesive with hard glue-line for parquet	B6	approx. 800 g/m ²	*
	SCHÖNOX® PARKETT 400 Universal wood adhesive for all kind of wood	B6	approx. 800 g/m ²	*
2-layer prefabricated parquet				
	SCHÖNOX® iLINE® 250 Shear-elastic parquet adhesive	SCHÖNOX iLINE APP	approx. 800 g/m ²	*
	SCHÖNOX® iLINE® 400 Universal wood adhesive for all kind of wood	SCHÖNOX iLINE APP	approx. 900 g/m ²	*
	SCHÖNOX® PARKETT 400 Universal wood adhesive for all kind of wood	B6 - B15	approx. 800 - 1200 g/m ²	*
	SCHÖNOX® PARKETT 250 Shear-elastic, waterless special adhesive for parquet	B6 - B15	approx. 850 - 1250 g/m ²	*

Floor Covering Installation

Covering	Adhesive	Tool / trowel acc. TKB	approx. consumption/m ²	Remark
3-layer prefabricated parquet				
	SCHÖNOX® iLINE® 250 Shear-elastic parquet adhesive	SCHÖNOX iLINE APP	approx. 800 g/m ²	*
	SCHÖNOX® iLINE® 400 Universal wood adhesive for all kind of wood	SCHÖNOX iLINE APP	approx. 900 g/m ²	*
	SCHÖNOX® PARKETT 600 Waterless universal SMP adhesive with hard glue-line for parquet	B11 - B15	approx. 1000 -1300 g/m ²	*
	SCHÖNOX® PARKETT 400 Universal wood adhesive for all kind of wood	B11 - B15	approx. 1000 -1200 g/m ²	*
	SCHÖNOX® PARKETT 250 Shear-elastic, waterless special adhesive for parquet	B11 - B15	approx. 1050 - 1250 g/m ²	*
Solid wood plank Wood type oak				Installation only on FLOOR and more® G 40
	SCHÖNOX® PARKETT 600 Waterless universal SMP adhesive with hard glue-line for parquet	B11 - B15	approx. 1000 -1300 g/m ²	* Obtain information on plank dimensions and decoupling

* Ensure that the backside of the parquet is wetting as completely as possible. In case of insufficient wetting, select the next largest trowel.

All adhesive fulfill EC1 PLUS acc. to GEV requirements, unless otherwise noted.

Please follow the technical information of relevant SCHÖNOX product data sheets, the advices of the manufactures of floor covering and also according to the well-known guidelines and instructions. If in doubt please do some practical tests or call the SCHÖNOX Productservice under phone +49 (0) 2547/910-325. More detailed information, product data sheets or laying instructions are available under www.schoenox.com or www.lindner-group.com