

Substrate Preparation

Substrate (for example)	Mastic asphalt screed acc. to DIN EN 13813 (AS)	Cement based screed acc. to DIN EN 13813 (CT)	Calciumsulfate- or calciumsulfate flowing screed acc. to DIN EN 13813(CA/CAF)	Dry screed
Primer (for example)	SCHÖNOX® SHP (not necessary if sufficient sanding)	SCHÖNOX® VD		
Self levelling compound (for example)	SCHÖNOX® HS 10 SCHÖNOX® HS 10 F SCHÖNOX® HS 50			SCHÖNOX® HS 10

Floor Covering Installation

Covering/ Collection	Adhesive	Tool/ trowel acc. TKB	Approx. consumption g/m ²	Remark
Parquet				Range of application
Junckers parquett and wood planks (900/1830/3700 x 129 x 22 mm) (1800/2100/2400 x 129 x 20,5 mm) (900/1830 x 129 x 13,8 mm)	SCHÖNOX® PARKETT 250 Shear-elastic, waterless special adhesive for parquet	TKB B15 - B17 - S4	approx. 1200 - 3000 g/m ²	
	SCHÖNOX® PARKETT 400 Universal wood adhesive for all kind of wood	TKB B15 - B17 - S4	approx. 1150 - 3000 g/m ²	

All adhesive fulfill EC1^{PLUS} acc. to GEV requirements, unless otherwise noted.

Please follow the technical information of relevant SCHÖNOX product data sheets, the advices of the manufactures of floor covering and also according to the well-known guidelines and instructions. If in doubt please do some practical tests or call the SCHÖNOX Productservice under phone +492547/910-325. More detailed information, product data sheets or laying instructions are available under www.schoenox.com or www.junckers.com