

## Substrate Preparation

Substrate (for example)	Mastic asphalt screed acc. to DIN EN 13813 (AS)	Cement based screed acc. to DIN EN 13813 (CT)	Calciumsulfate- or calciumsulfate flowing screed acc. to DIN EN 13813(CA/CAF)	Dry screed
Primer (for example)	SCHÖNOX® SHP (not necessary if sufficient sanding)	SCHÖNOX® VD		
Self levelling compound (for example)	SCHÖNOX® HS 10 SCHÖNOX® HS 10 F SCHÖNOX® HS 50			SCHÖNOX® HS 10

## Floor Covering Installation

Covering/ Collection	Adhesive	Tool/ trowel acc. TKB	Approx. consumption g/m <sup>2</sup>	Remark
<b>Designcovering (LVT)</b>	<b>Range of application</b>			
<b>Designer's LVT ONE Designer's LVT TWO Designer's LVT THREE</b>	<b>SCHÖNOX® DUROCOLL</b> Fibre reinforced, strong dispersion adhesive	TKB A1/A2	approx. 250 - 300 g/m <sup>2</sup>	
	<b>SCHÖNOX® PROTECT</b> Universal adhesive for highest loads	TKB A4	approx. 250 g/m <sup>2</sup>	increased heat exposure (for e.g. shop windows, conservatories); wet load
	<b>SCHÖNOX® PRO DESIGN</b> LVT Adhesive with long open time	TKB A1	approx. 220 g/m <sup>2</sup>	

All adhesive fulfill EC1<sup>PLUS</sup> acc. to GEV requirements, unless otherwise noted.

Please follow the technical information of relevant SCHÖNOX product data sheets, the advices of the manufactures of floor covering and also according to the well-known guidelines and instructions. If in doubt please do some practical tests or call the SCHÖNOX Productservice under phone +492547/910-325. More detailed information, product data sheets or laying instructions are available under [www.schoenox.com](http://www.schoenox.com) or <https://adramaq.jab.de>