

# SCHÖNOX® TACKIFIER

## Very low emission anti slip fixation

suitable for anti slip fixation of self-laying conductive and non conductive as well as antistatic carpet tiles with bitumen, non woven, PVC or PUR-backing as well as self-laying textile coverings in sheets on all suitable, water resistant substrates. For interior use.



## Product characteristics

- approved by the building authorities
- Emission tested building product according to ABG - approval no. Z-155.20-475
- EMICODE EC 1<sup>PLUS</sup>: very low emission
- for interior use
- solvent-free according to TRGS 610
- low consumption / high coverage
- suitable for castor wheels in accordance with EN 12 529
- suitable for application on subfloor heating systems
- can be applied by roller
- easy to apply
- long bonding
- suitable carpet-tiles can be replaced over a long period
- conductive adjustable

## Applications

**SCHÖNOX TACKIFIER is suitable for the fixation of:**

- textile tiles without surface tension (SL-Fliesen)
- conductive and antistatic textile carpet tiles in combination with SCHÖNOX LK (see product data sheet 7.07)
- loose laid textile sheet coverings on suitable substrates in interior areas.

## Requirements of substrate

- Adequate strength, load bearing capacity, dimensional stability and permanent dryness.
- Free of residues which reduce adhesion, e.g. dust, dirt, oil, fat and loose particles.
- For fixing floor coverings:
  - The existing floor should be checked for firm attachment to substrate, moisture-proof, closed surface and cleanliness. Old floors should be cleaned thoroughly.
- For fixation on calcium sulfate substrates, obtain for special information.

- In order to receive the substrate requirements of the specific coverings, refer to the technical product information of the coverings manufacturer.
- The requirements of the relevant valid standards, guidelines and data sheets apply.

## Recommended method of working

- SCHÖNOX TACKIFIER is a very low emission acrylic adhesive and tackifier and should be stirred before use.
- Coverings to be laid with SCHÖNOX TACKIFIER should be conditioned, unstressed and in a flat position.
- Spread the fixation evenly with a foam roller on the substrate. Avoid lumps of adhesive.
- Pay attention to a sufficient bonding.
- Carpet tiles are fixed in the "contact-phase" to make them more easily removeable.
- If in doubt, create a testing area or ask for special information.
- Laying stages:
  - "contact phase": adhesive film is transparent, but still tacky.
- To take up the covering:
  - To remove, the covering is slowly peeled away from the substrate.
- Direct securing to old adhesive residues can lead to interactions and thus to unpleasant smells.

## Packaging

- 10 kg plastic pail

## Storage

- Store SCHÖNOX TACKIFIER in cool, dry, frost-free conditions.
- Storage life of 1 year (in closed packaging).
- Opened packages should be closed immediately and used up as soon as possible.
- Remove any skin that has formed, do not stir in.

## Technical data

- Basis: synthetic special dispersion with bonding additives
- Density: 1,02 kg/l
- Storage temperature: not below + 5 °C
- Application temperature: not below + 15 °C floor temperature
- Material consumption:
  - roller: approx. 100 - 140 g/m<sup>2</sup>
- Waiting time: approx. 30 min
- Open time: up to 24 hours

All values are approximate, are subject to local climatic fluctuations and vary according to the absorbency of the substrates and the applicator device.

# SCHÖNOX® TACKIFIER

## Disposal

- Empty packaging completely and dispose of in accordance with regulations
- For the disposal of product residues, waste water and containers with adherent product residues please follow the local governmental regulations.

## EMICODE

- EC 1<sup>PLUS</sup>: very low emission

## GISCODE

- D1 - solvent-free dispersion adhesives and primers

## EPD - Self-declaration

Sika Deutschland GmbH declares that the product fulfills the criteria for dispersion based products of class a.

## ENVIRONMENTAL PRODUCT DECLARATION

acc. to ISO 14025 and EN 15804

## Owner of declaration

Deutsche Bauchemie e.V.  
 Industrieverband Klebstoffe e.V.  
 Verband der deutschen Lack- und Druckfarbenindustrie e.V.

## Editor

Institut für Bauen und Umwelt e.V. (IBU)

## Program owner

Institut für Bauen und Umwelt e.V. (IBU)

## Number of declaration

EPD-FEI-20160084-IBG1-DE

## Hazard class

- does not apply

## Instructions

- Clean tools immediately in water with low surface tension.
- Wipe impurities immediately from the covering surface and remove residual skin using a suitable cleaning agent (e.g. SCHÖNOX FIX CLEAN).
- Apply caps to protect the surface of the covering at the earliest after 72 hours.
- Follow the covering manufacturer's laying instructions. If in doubt, we recommend testing a small area.

- The BEB-leaflet "Beurteilen und Vorbereiten von Untergründen; Verlegen von elastischen und textilen Bodenbelägen, Schichtstoffelementen (Laminat), Parkett und Holzpflaster; Beheizte und unbeheizte Fußbodenkonstruktionen" should be followed.

The applicable recommendations, guidelines, DIN regulations and safety data sheets are to be observed, together with the recognised architectural and engineering regulations. We guarantee that our products leave the factory in perfect condition. While our recommendations for use are based on tests and practical experience, they can only provide general guidance without any assurance as to product characteristics, since we have no influence over the conditions on site, the execution of the work or the method of processing. This product data sheet supersedes all previous editions.



The Sika management system is certified to ISO 9001 and 14001 by SQS

**Sika Deutschland GmbH**

**Subsidiary Rosendahl**

**P.O. Box 11 40**

**D-48713 Rosendahl / Germany**

**Phone +49 (0) 2547-910-0**

**Fax +49 (0) 2547-910-101**

**E-mail: info@schoenox.de**

**www.schoenox.com**