



---

DECLARATION OF PERFORMANCE  
according annex III of the regulation (EU) No. 305/2011

for the product

**SCHÖNOX Q12**

No. 116041201

---

1. Unique identification code of the product type  
**EN 12004: C2 TE S2**
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR  
**batch number: see packaging of the product**
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer  
**Improved cementitious adhesive for tiling**
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5) of the CPR  
**Sika Deutschland GmbH  
Niederlassung Rosendahl  
Alfred-Nobel-Str. 6  
48720 Rosendahl / Germany**
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)  
**not applicable**
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V  
**Systeme 3 / Systeme 4 fire resistance**
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard  
**The notified body 0799 carried out the determination of the product type on the basis of type testing under sytem 3 and issued: test report. The Sika Deutschland GmbH performed the classification regarding reaction to fire according to system 4 on the basis of resolution 2010/81/EU of the EU Commission**
8. In the case the declaration of performance concerning a construction product for which a European Technical assessment has been issued  
**not applicable**

9. Declared performance

| Essential characteristics                          | Performance               | Harmonized technical specification |
|----------------------------------------------------|---------------------------|------------------------------------|
| Reaction to fire class                             | E                         | 12004:2007+A1:2012                 |
| Early tensile adhesion strength                    | n.a.                      | 12004:2007+A1:2012                 |
| Initial tensile adhesion strength                  | $\geq 1,0 \text{ N/mm}^2$ | 12004:2007+A1:2012                 |
| Tensile adhesion strength after water immersion    | $\geq 1,0 \text{ N/mm}^2$ | 12004:2007+A1:2012                 |
| Tensile adhesion strength after heat ageing        | $\geq 1,0 \text{ N/mm}^2$ | 12004:2007+A1:2012                 |
| Tensile adhesion strength after freeze-thaw cycles | $\geq 1,0 \text{ N/mm}^2$ | 12004:2007+A1:2012                 |
| Release of dangerous substances                    | See MSDS                  | 12004:2007+A1:2012                 |

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4

Signed for and on behalf of the manufacturer by

Rosendahl, 2017-01-25

Wolfgang Börsting, R&D Manager

Felix Meinert, R&D Lab Manager  
MTC

According Article 6(5) of the regulation (EU) No. 305/2011 an MSDS, conform to (EU) No. 1907/2006 (REACH) annex II, is attached to this Declaration of Conformity.