

# I SCHÖNOX Adhesive recommendation - Halbmond Teppichwerke



## Substrate Preparation

Substrate (for example)	Mastic asphalt screed acc. to DIN EN 13813 (AS)	Cement based screed acc. to DIN EN 13813 (CT)	Calciumsulfate- or calciumsulfate flowing screed acc. to DIN EN 13813(CA/CAF)	Dry screed
Primer(for example)	not necessary if sufficient sanding	SCHÖNOX VD		
Self levelling compound(for example)	SCHÖNOX HS 10 SCHÖNOX HS 10 F SCHÖNOX HS 50			SCHÖNOX HS 10

## Floor Covering Installation

Covering/ Collection	Adhesive	Tool/ trowel acc. TKB	Approx. consumption g/m <sup>2</sup>	Remark
<b>Textile coverings with second backs</b>				
	SCHÖNOX® EMICLASSIC ® Universal pressure sensitive dispersion adhesive	TKB B1	ca. 350g/m <sup>2</sup>	
	SCHÖNOX ® MULTIFLOOR Multi-purpose dispersion adhesive	TKB B1	ca. 370g/m <sup>2</sup>	
	SCHÖNOX® TEX OBJEKT® Textile covering dispersion adhesive	TKB B1	ca. 400g/m <sup>2</sup>	
<b>Textile coverings with fleece backs</b>				
	SCHÖNOX® EMICLASSIC ® Universal pressure sensitive dispersion adhesive	TKB B1	ca. 350g/m <sup>2</sup>	
	SCHÖNOX ® MULTIFLOOR Multi-purpose dispersion adhesive	TKB B1	ca. 370g/m <sup>2</sup>	
	SCHÖNOX® MULTIFIX Acrylic adhesive and tackifier	Rolle	ca. 150g/m <sup>2</sup>	
<b>Modular textile flooring systems with Easy-Lift coating</b>				
	SCHÖNOX® MULTIFIX Acrylic adhesive and tackifier	Rolle	ca. 150g/m <sup>2</sup>	

All adhesive fulfill EC1 PLUS acc. to GEV requirements, unless otherwise noted

Please follow the technical information of relevant SCHÖNOX product data sheets, the advices of the manufactures of floor covering and also according to the well-known guidelines and instructions. If in doubt please do some practical tests or call the SCHÖNOX Productservice under phone +02547/910-325. More detailed information, product data sheets or laying instructions are available under [www.schoenox.com](http://www.schoenox.com) or [www.halbmond.de](http://www.halbmond.de)