

Substrate Preparation

Substrate (for example)	Mastic asphalt screed acc. to DIN EN 13813 (AS)	Cement based screed acc. to DIN EN 13813 (CT)	Calciumsulfate- or calciumsulfate flowing screed acc. to DIN EN 13813(CA/CAF)	Dry screed
Primer (for example)	SCHÖNOX® SHP (not necessary if sufficient sanding)	SCHÖNOX® VD		
Self levelling compound (for example)	SCHÖNOX® HS 10 SCHÖNOX® HS 10 F SCHÖNOX® HS 50			SCHÖNOX® HS 10

Floor Covering Installation

Covering/ Collection	Adhesive	Tool/ trowel acc. TKB	Approx. consumption g/m ²	Remark
Solid Plank Floors	Parquet Adhesives			Range of Application
Oak HeartOak	SCHÖNOX® PARKETT 400 Universal wood adhesive for all kind of wood	TKB B6 - B15	approx. 800 - 1200 g/m ²	
	SCHÖNOX® PARKETT 600 Waterless universal SMP adhesive with hard glue-line for parquet	TKB B6 - B15	approx. 800 - 1200 g/m ²	
Pine Ash Douglas	SCHÖNOX® PARKETT 400 Universal wood adhesive for all kind of wood	TKB B6 - B15	approx. 800 - 1200 g/m ²	Thickness-to-width ratio: max. 1:10
	SCHÖNOX® PARKETT 600 Waterless universal SMP adhesive with hard glue-line for parquet	TKB B6 - B15	approx. 800 - 1200 g/m ²	
Engineered Floor	Parquet Adhesives			
Layers Oak	SCHÖNOX® iLINE® 250 Shear-elastic parquet adhesive	SCHÖNOX iLINE APP	approx. 800 g/m ²	
	SCHÖNOX® PARKETT 250 Shear-elastic, waterless special adhesive for parquet	TKB B6 - B15	approx. 850 - 1250 g/m ²	
	SCHÖNOX® PARKETT 400 Universal wood adhesive for all kind of wood	TKB B6 - B15	approx. 800 - 1200 g/m ²	
Pattern Floors	Parquet Adhesives			Range of Application
Douglas Pattern Oak Pattern	SCHÖNOX® PARKETT 400 Universal wood adhesive for all kind of wood	TKB B6 - B10	approx. 800 - 900 g/m ²	Thickness-to-width ratio: max. 1:10
	SCHÖNOX® PARKETT 600 Waterless universal SMP adhesive with hard glue-line for parquet	TKB B6/ B10	approx. 800 g/m ²	

All adhesive fulfill EC1^{PLUS} acc. to GEV requirements, unless otherwise noted.

Please follow the technical information of relevant SCHÖNOX product data sheets, the advices of the manufactures of floor covering and also according to the well-known guidelines and instructions. In if doubt please do some practical tests or call the SCHÖNOX Productservice under phone +492547/910-325. More detailed information, product data sheets or laying instructions are available under www.schoenox.com or www.dinesen.com