

**Substrate Preparation**

Substrate (for example)	Mastic asphalt screed acc. to DIN EN 13813 (AS)	Cement based screed acc. to DIN EN 13813 (CT)	Calciumsulfate- or calciumsulfate flowing screed acc. to DIN EN 13813(CA/CAF)	Dry screed
Primer (for example)	SCHÖNOX® SHP (not necessary if sufficient sanding)		SCHÖNOX® VD	
Self levelling compound (for example)	SCHÖNOX® HS 10 SCHÖNOX® HS 10 F SCHÖNOX® HS 50			SCHÖNOX® HS 10

**Floor Covering Installation**

Covering/ Collection	Adhesive	Tool/ trowel acc. TKB	Approx. consumption g/m <sup>2</sup>	Remark
				Range of application
Entryway	<b>SCHÖNOX® DUROCOLL</b> Fibre reinforced, strong dispersion adhesive	TKB A2	approx 300 g/m <sup>2</sup>	
Carpet	<b>SCHÖNOX® PU 900</b> Solvent-free 2-component polyurethane adhesive	TKB A1	approx 300 g/m <sup>2</sup>	increased stress
<b>Designcoverings</b>				
Signature Spacia Designers' Choice Form Access	<b>SCHÖNOX® iFLOOR®</b> Dispersion based rollable adhesive	special roller	approx 120 g/m <sup>2</sup> (including special primer)	
	<b>SCHÖNOX® DUROCOLL</b> Fibre reinforced, strong dispersion adhesive	TKB A1/A2	approx 250 - 300 g/m <sup>2</sup>	
	<b>SCHÖNOX® PU 900</b> Solvent-free 2-component polyurethane adhesive	TKB A1 - A4	approx 300 - 400 g/m <sup>2</sup>	increased stress
Acoustic Cirro First	<b>SCHÖNOX® DUROCOLL</b> Fibre reinforced, strong dispersion adhesive	TKB A1/A2	approx 250 - 300 g/m <sup>2</sup>	
	<b>SCHÖNOX® PU 900</b> Solvent-free 2-component polyurethane adhesive	TKB A1 - A4	approx 300 - 400 g/m <sup>2</sup>	increased stress
Marine	<b>SCHÖNOX® iFLOOR®</b> Dispersion based rollable adhesive	special roller	approx 120 g/m <sup>2</sup> (including special primer)	
	<b>SCHÖNOX® DUROCOLL</b> Fibre reinforced, strong dispersion adhesive	TKB A1/A2	approx 250 - 300 g/m <sup>2</sup>	

All adhesive fulfill EC1<sup>PLUS</sup> acc. to GEV requirements, unless otherwise noted

Please follow the technical information of relevant SCHÖNOX product data sheets, the advices of the manufactures of floor covering and also according to the well-known guidelines and instructions. If in doubt please do some practical tests or call the SCHÖNOX Productservice under phone +492547/910-325. More detailed information, product data sheets or laying instructions are available under [www.schoenox.com](http://www.schoenox.com) or [www.amtico.com](http://www.amtico.com)