

Substrate Preparation

Substrate (for example)	Cement based screed acc. to DIN EN 13813 (CT)	Concrete (residual moisture ≤ 3,5 Gew.-%)	Concrete 3 month (Residual moisture ≤ 10 Gew.-%)	concrete 6 month (Residual moisture ≤ 6,0 Gew.-%)
Primer (for example)	none	none	SCHÖNOX® EPB	SCHÖNOX® HP RAPID

Floor Covering Installation

Covering/ Collection	Adhesive	Tool/ trowel acc. TKB	Approx. consumption g/m ²	Remark
Loose lay installation				Range of application
GTI MAX	SCHÖNOX® PU 900 Solvent-free 2-component polyurethane adhesive	TKB A1/A2	approx. 450 - 500 g/m ²	Entrances and exits of halls as well as hall transitions
	SCHÖNOX® PROTECT Universal adhesive for highest loads	TKB A1/A2	approx. 360 - 370 g/m ²	
	SCHÖNOX® MULTIFIX Acrylic Adhesive and Tackifier	TKB A4	approx. 150 g/m ²	Smooth surfaces and/or manoeuvring in confined spaces
Attraction®	SCHÖNOX® PU 900 Solvent-free 2-component polyurethane adhesive	TKB A1/A2	approx. 450 - 500 g/m ²	Bonding of ramps and corners under fork-lift truck load
	SCHÖNOX® PROTECT Universal adhesive for highest loads	TKB A1/A2	approx. 360 - 370 g/m ²	
Fixation				
Creation 70 connect	SCHÖNOX® MULTIFIX Acrylic Adhesive and Tackifier	TKB A4	approx. 150 g/m ²	
Glue down installation				
GTI MAX Attraction®	SCHÖNOX® PU 900 Solvent-free 2-component polyurethane adhesive	TKB A1/A2	approx. 450 - 500 g/m ²	
	SCHÖNOX® PROTECT Universal adhesive for highest loads	TKB A1/A2	approx. 360 - 370 g/m ²	
Creation 70 connect	SCHÖNOX® PU 900 Solvent-free 2-component polyurethane adhesive	TKB A1/A2	approx. 450 - 500 g/m ²	In hygienic areas, with high thermal or mechanical load
	SCHÖNOX® PROTECT Universal adhesive for highest loads	TKB A1/A2	approx. 360 - 370 g/m ²	

Floor Covering Installation

Covering/ Collection	Adhesive	Tool/ trowel acc. TKB	Approx. consumption g/m ²	Remark
Laying on SCHÖNOX TRENNLAGE				Range of application
GTI MAX	SCHÖNOX® PU 900 Solvent-free 2-component polyurethane adhesive	TKB A1/A2	approx. 450 - 500 g/m ²	In areas where loose laying is permissible, only hall entrances and exits as well as hall transitions need to be bonded.
	SCHÖNOX® PROTECT Universal adhesive for highest loads	TKB A1/A2	approx. 360 - 370 g/m ²	
	SCHÖNOX® MULTIFIX Acrylic Adhesive and Tackifier	TKB A4	approx. 150 g/m ²	For smooth subfloors and/or manoeuvring in confined spaces in areas where loose laying is permitted.

It is essential to follow the Gerflor installation instructions for the individual coverings and installation types. This applies in particular to the specified load limits. For loads and applications exceeding these limits, it is essential to obtain a project-specific installation recommendation from the SAT Service Application Technology of Gerflor Mipolam GmbH and the SCHÖNOX Productservice.

All adhesive fulfill EC1^{PLUS} acc. to GEV requirements, unless otherwise noted.

Please follow the technical information of relevant SCHÖNOX product data sheets, the advices of the manufactures of floor covering and also according to the well-known guidelines and instructions. If in doubt please do some practical tests or call the SCHÖNOX Productservice under phone +02547/910-325. More detailed information, product data sheets or laying instructions are available under www.schoenox.com or www.gerflor.com