

## Substrate Preparation

Substrate (for example)	Mastic asphalt screed acc. to DIN EN 13813 (AS)	Cement based screed acc. to DIN EN 13813 (CT)	Calciumsulfate- or calciumsulfate flowing screed acc. to DIN EN 13813(CA/CAF)	Dry screed
Primer (for example)	SCHÖNOX® SHP (not necessary if sufficient sanding)	SCHÖNOX® VD		
Self levelling compound (for example)	SCHÖNOX® HS 10 SCHÖNOX® HS 10 F SCHÖNOX® HS 50			SCHÖNOX® HS 10

## Floor Covering Installation

Covering/ Collection	Adhesive	Tool/ trowel acc. TKB	Approx. consumption g/m <sup>2</sup>	Remark
<b>Range of application</b>				
NORAMENT (smooth backing)	<b>SCHÖNOX® PROTECT</b> Universal adhesive for highest loads	TKB A1	approx. 360 g/m <sup>2</sup>	
	<b>SCHÖNOX® EMICLASSIC®</b> Universal pressure sensitive dispersion adhesive	TKB A1/A2	approx. 250 - 300 g/m <sup>2</sup>	Covering thickness up to 4 mm
	<b>SCHÖNOX® PU 900</b> Solvent-free 2-component polyurethane adhesive	TKB A2	approx. 500 g/m <sup>2</sup>	increased heat exposure (for e.g. shop windows, conservatories); wet load
NORAMENT (smooth backing), conductive	<b>SCHÖNOX® COMBILEIT®</b> Conductive universal adhesive for all conductive coverings	notched trowel, fine	approx. 300 g/m <sup>2</sup>	
NORAPLAN NORACARE NORAPLAN acoustic	<b>SCHÖNOX® EMICLASSIC®</b> Universal pressure sensitive dispersion adhesive	TKB A2	approx. 300 g/m <sup>2</sup>	
NORAPLAN, conductive	<b>SCHÖNOX® COMBILEIT®</b> Conductive universal adhesive for all conductive coverings	notched trowel, fine	approx. 300 g/m <sup>2</sup>	
NORAPLAN, conductive 3,5 mm, surgical flooring, sheets	<b>SCHÖNOX® COMBILEIT®</b> Conductive universal adhesive for all conductive coverings	notched trowel, fine	approx. 300 g/m <sup>2</sup>	Maximum load 5 N/mm <sup>2</sup> * *For higher loads use NORAMENT or consult with /nora

All adhesive fulfill EC1<sup>PLUS</sup> acc. to GEV requirements, unless otherwise noted

Please follow the technical information of relevant SCHÖNOX product data sheets, the advices of the manufactures of floor covering and also according to the well-known guidelines and instructions. If in doubt please do some practical tests or call the SCHÖNOX Productservice under phone +02547/910-325. More detailed information, product data sheets or laying instructions are available under [www.schoenox.com](http://www.schoenox.com) or [www.nora.com](http://www.nora.com)