

Substrate Preparation

Substrate (for example)	Mastic asphalt screed acc. to DIN EN 13813 (AS)	Cement based screed acc. to DIN EN 13813 (CT)	Calciumsulfate- or calciumsulfate flowing screed acc. to DIN EN 13813(CA/CAF)	Dry screed
Primer (for example)	SCHÖNOX® SHP (not necessary if sufficient sanding)	SCHÖNOX® VD		
Self levelling compound (for example)	SCHÖNOX® HS 10 SCHÖNOX® HS 10 F SCHÖNOX® HS 50			SCHÖNOX® HS 10

Floor Covering Installation

Covering/Collection	Adhesive	Tool/trowel acc. TKB	approx. consumption g/m ²	Remark
Design Floor				Range of application
floors@work 55 floors@work 80 floors@home 20 floors@home 30 floors@home 40	SCHÖNOX® DUROCOLL Fibre reinforced, strong dispersion adhesive	TKB A1	approx. 250 - 300 g/m ²	
	SCHÖNOX® IFLOOR® Dispersion based rollable adhesive	roller	approx. 80 g/m ²	

All adhesive fulfill EC1^{PLUS} acc. to GEV requirements, unless otherwise noted.

Please follow the technical information of relevant SCHÖNOX product data sheets, the advices of the manufactures of floor covering and also according to the well-known guidelines and instructions. If in doubt please do some practical tests or call the SCHÖNOX Productservice under phone +49 (0) 2547/910-325. More detailed information, product data sheets or laying instructions are available under www.schoenox.com or www.project-floors.com.