

Substrate Preparation

Substrate (for example)	Mastic asphalt screed acc. to DIN EN 13813 (AS)	Cement based screed acc. to DIN EN 13813 (CT)	Calciumsulfate- or calciumsulfate flowing screed acc. to DIN EN 13813(CA/CAF)	Dry screed
Primer (for example)	SCHÖNOX® SHP (not necessary if sufficient sanding)	SCHÖNOX® VD		
Self levelling compound (for example)	SCHÖNOX® HS 10 SCHÖNOX® HS 10 F SCHÖNOX® HS 50			SCHÖNOX® HS 10

Floor Covering Installation

Covering/ Collection	Adhesive	Tool/ trowel acc. TKB	Approx. consumption g/m ²	Remark
Design flooring (LVT)				Range of application
MODULEO	SCHÖNOX® iFLOOR® Dispersion based rollable adhesive	special roller	approx. 120 g/m ² (including special primer)	
	SCHÖNOX® DUROCOLL Fibre reinforced, strong dispersion adhesive	TKB A1/A2	approx. 250 - 300 g/m ²	
	SCHÖNOX® PU 900 Solvent-free 2-component polyurethane adhesive	TKB A1	approx. 400 g/m ²	increased heat exposure (for e.g. shop windows, conservatories); wet load
Heterogeneous flooring				
Heterogeneous object floor coverings (HV)	SCHÖNOX® EMICLASSIC® Universal pressure sensitive dispersion adhesive	TKB A1/A2	approx. 300 - 350 g/m ²	
	SCHÖNOX® MULTI FLOOR Very low emission, multi-purpose dispersion adhesive	TKB A1/A2	approx. 300 - 350 g/m ²	
Textile floor coverings				
Carpet tiles with NXT backing	SCHÖNOX® EMICLASSIC® Universal pressure sensitive dispersion adhesive	TKB A2	approx. 280 g/m ²	
	SCHÖNOX® MULTIFIX Acrylic Adhesive and Tackifier	roller	approx. 100 - 200 g/m ²	
Carpet tiles with bitumen backing	SCHÖNOX® TACKIFIER Very low emission anti slip fixation	roller	approx. 100 g/m ²	
	SCHÖNOX® MULTIFIX Acrylic Adhesive and Tackifier	roller	approx. 100 - 200 g/m ²	
	SCHÖNOX® TEX XTREME Textile covering dispersion adhesive	TKB A2	approx. 350 g/m ²	

Floor Covering Installation

Covering/ Collection	Adhesive	Tool/ trowel acc. TKB	Approx. consumption g/m ²	Remark
Textile floor coverings				Range of application
Textile tiles with EcoFlex backing	SCHÖNOX® MULTIFIX Acrylic Adhesive and Tackifier	roller	approx. 100 - 200 g/m ²	
	SCHÖNOX® TEX XTREME Textile covering dispersion adhesive	TKB B1/B2	approx. 400 - 490 g/m ²	
	SCHÖNOX® EMICLASSIC® Universal pressure sensitive dispersion adhesive	TKB B1/B2	approx. 350 - 400 g/m ²	

All adhesive fulfill EC1^{PLUS} acc. to GEV requirements, unless otherwise noted

Please follow the technical information of relevant SCHÖNOX product data sheets, the advices of the manufactures of floor covering and also according to the well-known guidelines and instructions. If in doubt please do some practical tests or call the SCHÖNOX Productservice under phone +02547/910-325. More detailed information, product data sheets or laying instructions are available under www.schoenox.com or www.ivcgroup.com