



---

DECLARATION OF PERFORMANCE  
according annex III of the regulation (EU) No. 305/2011

for the product

## **SCHÖNOX EA PUR**

No. 316041101

---

1. Unique identification code of the product type  
**EN 14891: RM O2 P**
  
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR  
**batch number: see packaging of the product**
  
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer  
**Liquid applied water impermeable product for internal and external installations on walls and floors beneath ceramic tiling**
  
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5) of the CPR  
**Sika Deutschland GmbH  
Niederlassung Rosendahl  
Alfred-Nobel-Str. 6  
48720 Rosendahl / Germany**
  
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)  
**not applicable**
  
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V  
**Systeme 3**
  
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard  
**The notified body 0761 carried out the determination of the product type on the basis of type testing and issued a test report.**
  
8. In the case the declaration of performance concerning a construction product for which a European Technical assessment has been issued  
**not applicable**

## 9. Declared performance

Essential characteristics	Performance	Harmonized technical specification
Initial tensile adhesion strength	$\geq 0,5 \text{ N/mm}^2$	EN 14891:2012
Tensile strength after water contact	$\geq 0,5 \text{ N/mm}^2$	EN 14891:2012
Tensile strength after heat ageing	$\geq 0,5 \text{ N/mm}^2$	EN 14891:2012
Tensile strength after freeze-thaw-cycles	$\geq 0,5 \text{ N/mm}^2$	EN 14891:2012
Tensile strength after contact with lime water	$\geq 0,5 \text{ N/mm}^2$	EN 14891:2012
Tensile strength after contact with chloride water	$\geq 0,5 \text{ N/mm}^2$	EN 14891:2012
Waterproofing	no penetration	EN 14891:2012
Crack bridging ability	$\geq 0,75 \text{ mm}$	EN 14891:2012
Release of dangerous substances	See MSDS	EN 14891:2012

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4

Signed for and on behalf of the manufacturer by

Rosendahl, 2017-01-24

Wolfgang Börsting, R&D Manager

Felix Meinert, R&D Lab Manager  
MTC

According Article 6(5) of the regulation (EU) No. 305/2011 an MSDS, conform to (EU) No. 1907/2006 (REACH) annex II, is attached to this Declaration of Conformity.