


SCHÖNOX® iLINE® APP

Battery powered applicator for the SCHÖNOX iLINE system

for the efficient, ergonomic and clean treatment of SCHÖNOX iLINE adhesives in tubular bags. Cordless power unit is integrated. Removeable blast pipes in two different sizes are available. Quick change of blast pipes without tools.



Product characteristics

- within the same working time laying more m² of parquet
- clean work - in practice no adhesive residues on hands and on parquet
- component of SCHÖNOX iLINE
- no connecting cable
- ergonomic working in upright position
- easy handling
- minor cleaning work thanks to practical removeable blast pipe
- quick change of blast pipes without tools
- practical guidance function
- easy change of tubular bags
- precise dosing possible

Applications

to work with:

- SCHÖNOX iLINE parquet adhesive

Recommended method of working

- Place SCHÖNOX iLINE APP on the subfloor.
- Apply the adhesive evenly with SCHÖNOX iLINE APP to the substrate using the blast pipe. If wetting is insufficient adjust the bore diameter of the blast pipe or slow down the spreading speed.
- Use the wall or the edge of the parquet as side lay for the blast pipe to pull the applicator across the subfloor.
- Thereby press the push button to apply the adhesive in even crawlers.
- Stop in front of the opposite wall. Turn the applicator and apply the adhesive on the left area.
- As the power unit has stopped, short reverse running starts automatically to reduce pressure.
- Let adhesive drip off from the nozzle.
- Lift the device and lean against the wall. Take care to use an underlay in case adhesive drips off.

- The crawlers must build a straight and even line.
- If the conveyor output is too high, the adhesive builds sinuous lines. In this case reduce the conveyor output or move the applicator faster along the subfloor.

Packaging

- SCHÖNOX iLINE APP in paper transport box including:
 - SCHÖNOX iLINE AK 290
 (Especially for narrow types of parquet such as mosaic parquet)
 Wide nozzle strip: 290 mm
 Bore diameter: 15 mm
- SCHÖNOX iLINE AK 380
 Wide nozzle strip: 380 mm
 Bore diameter: 10 mm
- instructions and safety manual

Component parts

- SCHÖNOX iLINE APP BOX inclusive:
 - PTFE-Spray
 - all-purpose adhesive tape
- SCHÖNOX iLINE AK 290
- SCHÖNOX iLINE AK 380

Instructions

- The enclosed operating instructions and safety regulations must be observed.
- Clean tools immediately after use with SCHÖNOX FIX CLEAN.
- After a longer period of not using the tool, still filled with a broached cubular bag, check the through hole to the blast pipe and remove stopper.
- Hardened material can only be removed mechanically.
- The product data sheets of further add-on products should be observed.



SCHÖNOX® iLINE® APP

The applicable recommendations, guidelines, DIN regulations and safety data sheets are to be observed, together with the recognised architectural and engineering regulations. We guarantee that our products leave the factory in perfect condition. While our recommendations for use are based on tests and practical experience, they can only provide general guidance without any assurance as to product characteristics, since we have no influence over the conditions on site, the execution of the work or the method of processing. This product data sheet supersedes all previous editions.



The Sika management system is certified to ISO 9001 and 14001 by SQS

Sika Deutschland GmbH

Subsidiary Rosendahl

P.O. Box 11 40

D-48713 Rosendahl / Germany

Phone +49 (0) 2547-910-0

Fax +49 (0) 2547-910-101

E-mail: info@schoenox.de

www.schoenox.com