

PRODUCT DATA SHEET

Sikafloor® VSP Therm

Optional pre-assembled pump for fixed value control in Sikafloor® VS Therm 2-15.

DESCRIPTION

Sikafloor® VSP Therm is a pre-assembled pump unit for fixed value control. Sikafloor® VSP Therm enables the circulation of heating water from the primary circuit by maintaining the temperature at a preset value using a mixing valve with a thermostatic element.

USES

Sikafloor® VSP Therm is only suitable in combination with Sikafloor® VS Therm 2-15. Sikafloor® VSP Therm is used in particular when connection to an old heating system with an excessively high flow temperature for underfloor heating is planned.

FEATURES

The following properties only apply in conjunction with Sikafloor® VS Therm 2-15:

- Connection of underfloor heating to an existing heating system with excessively high flow temperature.

PRODUCT INFORMATION

Packaging	1 piece installed in Sikafloor® VS Therm 2-15
Colour	white
Shelf life	-
Storage conditions	-
Operating temperature range	5-90 °C
Max. operating pressure	10 bar
Temperature control range	20-55 °C

SYSTEM INFORMATION

System structure	Sikafloor® VSP Therm is a system component and is supplied in Sikafloor® VS Therm 2-15.
System	Sikafloor® VSP Therm, in combination with Sikafloor® VS Therm, is a component of the following systems: <ul style="list-style-type: none"> ▪ SCHÖNOX RENOTHERM SYSTEM ▪ THOMSIT HYDRO-HEAT SYSTEM

BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

FURTHER DOCUMENTATION

- System brochure SCHÖNOX RENOTHERM
- System brochure THOMSIT HYDRO-HEAT
- Datasheet Sikafloor VS Therm

APPLICATION

The electrical connection of Sikafloor® VSP Therm is carried out by qualified personal.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Deutschland CH AG & Co KG

Kornwestheimer Straße 103 - 107
D - 70439 Stuttgart
Tel.: +49 711 8009-0
Fax: +49 711 8009-321
info@de.sika.com
www.sika.de

SikafloorVSPTherm-en-DE-(02-2026)-2-1.pdf

PRODUCT DATA SHEET

Sikafloor® VSP Therm
February 2026, Version 02.01
020816990050245041