

## PRODUCT DATA SHEET

# Sarnafil® T Point Flashing

Prefabricated FPO flat roof Point Flashing

## DESCRIPTION

Sarnafil® T Point Flashing is a prefabricated injection moulded roof point flashing based on a flexible polyolefin (FPO) with fitted integrated heat shrink sleeve.

## USES

- Post flashing on Sarnafil® flat roof systems

## CHARACTERISTICS / ADVANTAGES

- Resistant to UV exposure
- Easy and safe application
- Heat weldable
- Fitted integrated heat shrink sleeve



## PRODUCT INFORMATION

<b>Composition</b>	<ul style="list-style-type: none"><li>▪ Injection moulding: Flexible polyolefins (FPO) based on polypropylene (PP)</li><li>▪ Heat shrink sleeve: Cross-linked polyolefins</li></ul>			
<b>Packaging</b>	Depending on the order quantity, the products are packaged on pallets or in cartons.			
<b>Shelf life</b>	If stored under proper conditions, the product keeps its performance.			
<b>Storage conditions</b>	Store in original, unopened and undamaged sealed packaging in dry conditions at temperatures between +5 °C and +30 °C. Always refer to packaging. Do not stack pallets of rolls or any other material on top during transport or storage.			
<b>Appearance and colour</b>	<b>Surface</b>	<b>Smooth</b>		
	<b>Colour</b>	Beige Grey (nearest RAL 7040) other colours on request		
<b>Dimensions</b>	<b>Inside pipe conical diameter</b>	<b>Diameter base plate</b>	<b>Height</b>	<b>Thickness</b>
	17 mm	180 mm	250 mm	2 mm
	20 mm (+/- 1 mm)	(+/- 5 mm)	(+5/-10 mm)	(+0,2/-0,1 mm)
	21 mm	180 mm	250 mm	2 mm
	24 mm (+/- 1 mm)	(+/- 5 mm)	(+5/-10 mm)	(+0,2/-0,1 mm)

## SYSTEM INFORMATION

<b>System structure</b>	Compatible products: <ul style="list-style-type: none"><li>▪ Sarnafil® AT/TG/TS membranes</li></ul>
-------------------------	---

## APPLICATION INFORMATION

<b>Ambient air temperature</b>	-20 °C min. / +60 °C max.
<b>Substrate temperature</b>	-30 °C min. / +60 °C max.

## BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## FURTHER INFORMATION

### Installation instructions

Refer to 'Sarnafil® flat roof waterproofing membranes'.

## IMPORTANT CONSIDERATIONS

Installation work must only be carried out by Sika® trained and approved contractors, experienced in this type of application.

- The use of Sarnafil® T Point Flashing is limited to geographical locations with average monthly minimum temperatures of -50 °C. Permanent ambient temperature during use is limited to +50 °C.
- Installation of ancillary products, e.g. contact adhes-

ives / cleaners is limited to temperatures above +5 °C. Refer to relevant Product Data Sheets for further information.

## ECOLOGY, HEALTH AND SAFETY

### REGULATION (EC) NO 1907/2006 - REACH

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

# APPLICATION INSTRUCTIONS

## APPLICATION METHOD / TOOLS

### Installation procedure

#### Prefabricated Point Flashing

Reference must be made to further documentation where applicable, such as relevant method statement, application manual and installation or working instructions.

#### Heat shrink sleeve

Remove the red transportation lock. Position the sleeve in the centre. Heat the sleeve with a heating gun (e.g. Leister Triac). Gun air temperature > 120 °C.

## LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

#### Sika Deutschland GmbH

Roofing  
Kornwestheimer Strasse 103-107  
70439 Stuttgart  
Tel.: +49 711/8009-0  
roofing@de.sika.com  
www.sika.de/dachabdichtung



#### PRODUCT DATA SHEET

Sarnafil® T Point Flashing  
August 2022, Version 02.01  
020945032100001005

SarnafilTPointFlashing-en-DE-(08-2022)-2-1.pdf