

PRODUCT DATA SHEET

Sarnafil® T Post Flashing

Prefabricated FPO flat roof post flashing

DESCRIPTION

Sarnafil® T Post Flashing is a prefabricated roof post flashing based on an FPO waterproofing membrane.

USES

Sarnafil® T Post Flashing may only be used by experienced professionals.

- Post flashing on Sarnafil® flat roof systems


CHARACTERISTICS / ADVANTAGES

- Resistant to UV exposure
- Easy and safe application
- Heat weldable

Type P5 (closed pipe)



Type P6 (open pipe)



PRODUCT INFORMATION

Composition	Flexible polyolefin (FPO) based on polypropylene (PP)		
Packaging	Depending on the order quantity and product size, the products are packaged on pallets or in cartons.		
Shelf life	If stored under proper conditions, the product keeps its performance.		
Storage conditions	Store in original, unopened and undamaged sealed packaging in dry conditions at temperatures between +5 °C and +30 °C. Always refer to packaging. Do not stack pallets of rolls or any other material on top during transport or storage.		
Appearance and colour	Surface:	Smooth	
	Colour:	Beige	
		Grey (nearest RAL 7040)	
		other colours on request	
Dimensions	Type P5 / Type P6		
	Inside diameter	Sleeve height	Base plate diameter
	23 mm	300 mm	210 mm
	29 mm		
	35 mm		
	44 mm		
	49 mm		
	Other diameters on request		

SYSTEM INFORMATION

System structure	The following system products must be used: <ul style="list-style-type: none">▪ Sarnafil® AT types▪ Sarnafil® TG 66-types▪ Sarnafil® TG 76-types▪ Sarnafil® TS 77-types
-------------------------	--

TECHNICAL INFORMATION

Reaction to fire	Class E	(EN 11925-2, Classification to EN 13501-1)
-------------------------	---------	--

APPLICATION INFORMATION

Ambient air temperature	-20 °C min. / +60 °C max.
Substrate temperature	-30 °C min. / +60 °C max.

BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

FURTHER INFORMATION

- Installation instructions: Sarnafil® flat roof waterproofing membranes.

IMPORTANT CONSIDERATIONS

Installation work must only be carried out by Sika® trained and approved contractors, experienced in this type of application.

- The use of Sarnafil® T Post Flashing is limited to geographical locations with average monthly minimum temperatures of -50 °C. Permanent ambient temperature during use is limited to +50 °C.
- Installation of ancillary products, e.g. contact adhesives / cleaners is limited to temperatures above +5 °C. Refer to relevant Product Data Sheets for further information.

ECOLOGY, HEALTH AND SAFETY

REGULATION (EC) NO 1907/2006 - REACH

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

APPLICATION INSTRUCTIONS

APPLICATION METHOD / TOOLS

Installation procedure

Reference must be made to further documentation where applicable, such as relevant method statement, application manual and installation or working instructions.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Deutschland GmbH

Roofing
Kornwestheimer Strasse 103-107
70439 Stuttgart
Tel.: +49 711/8009-0
roofing@de.sika.com
www.sika.de/dachabdichtung



PRODUCT DATA SHEET

Sarnafil® T Post Flashing
August 2022, Version 01.01
020945032100001001

SarnafilTPostFlashing-en-DE-(08-2022)-1-1.pdf