

SikaProof® A+ 12

UNIQUE IDENTIFICATION

DECLARATION OF PERFORMANCE

No. 16273116

1

	CODE OF THE PRODUCT- TYPE:	16273116
2	INTENDED USE/S	EN 13967:2012 Plastic and rubber sheets intended for use as damp proofing in buildings
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich

4 AUTHORISED REPRESENTATIVE:

5 SYSTEM/S OF AVCP: System 2+ System 3

6a HARMONISED STANDARD: EN 13967:2012

Notified body/ies: 1213

16273116 2019.03 , ver. 2 1005, 1193

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification	
Reaction to fire	Class E	System 3		
Watertightness	Pass	System 2+		
Tear resistance:	NPD			
Joint strength	≥ 100 N/50 mm	System 2+		
Impact resistance	≥ 400 mm	System 2+		
Tensile strength ¹ :			<u> </u>	
Machine direction	≥ 15 N/mm ²	System 2+		
Cross direction	≥ 12 N/mm ²		EN	
Resistance to static loading	NPD	System 2+	13967:2012 	
Durability: Watertightness after artificial ageing Watertightness after exposure to chemicals	Pass Pass	System 2+		
Dangerous substances	NPD	System 2+		

¹Based on single membrane only

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Tomasz Gutowski

Function: Corporate Standardization

and Approvals

At Warsaw on 10 October 2019

Name: Tatiana Ageyeva

Function: Standardization and Approvals

At Warsaw on 10 October 2019

End of information as required by Regulation (EU) No 305/2011



1005, 1193



19

Sika Services AG, Zurich, Switzerland

DoP No. 16273116

EN 13967:2012

Notified Body 1213

Plastic and rubber sheets intended for use as damp proofing in buildings

Reaction to fire Class E Watertightness Pass

Joint strength ≥ 100 N/50 mm

Impact resistance ≥ 400 mm

Tensile strength¹:

Machine direction $\ge 15 \text{ N/mm}^2$ Cross direction $\ge 12 \text{ N/mm}^2$

Durability:

Watertightness after artificial ageing

Watertightness after exposure to

chemicals

Pass

Pass

http://dop.sika.com

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance SikaProof® A+ 12 16273116 2019.03 , ver. 2 1005, 1193 Template for translation. Only for internal use



¹Based on single membrane only

Sika Services AG Tüffenwies 16-22 8064 Zürich Switzerland www.sika.com

Declaration of Performance SikaProof® A+ 12 16273116 2019.03 , ver. 2 1005, 1193 Template for translation. Only for internal use

