

## PRODUCT DATA SHEET

# Sikalastic® Rapid Fleece 110 Perforated

Perforated synthetic fibre-fleece insert for reinforcement and layer thickness control of the Sikalastic® Rapid-722/-722 Detail waterproofing system.

### DESCRIPTION

Sikalastic® Rapid Fleece 110 Perforated is a system fleece insert made of synthetic fibre-fleece for liquid waterproofing.

### USES

Sikalastic® Rapid Fleece 110 Perforated is used as an insert in the Sikalastic® Rapid-72 /-722 Detail waterproofing system.

### FEATURES

- simple and fast processing in the area and for detailed solutions
- increases the crack-bridging ability of the systems
- ensures the required dry film thickness
- high tear strength, high elasticity
- improved fleece soaking

### PRODUCT INFORMATION

Composition	Mechanically strengthened and heat-set special synthetic-fibre fleece	
Packaging	Rolls	
Appearance and colour	white	
Shelf life	In unopened and undamaged original packaging, the product retains its properties.	
Storage conditions	Store Sikalastic® Rapid Fleece 110 Perforated in a horizontal position. Protect from direct sunlight, rain and snow.	
Dimensions	Length	50 m
	Width	0.2 m (10 m <sup>2</sup> )
		0.26 m (13 m <sup>2</sup> )
		0.35 m (17.5 m <sup>2</sup> )
		0.52 m (26 m <sup>2</sup> )
		1.05 m (52.5 m <sup>2</sup> )
Mass per unit area	110 g/m <sup>2</sup>	

### BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

### ECOLOGY, HEALTH AND SAFETY

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the

article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

## APPLICATION

1. Prepare fleece cuttings according to the conditions of the area to be sealed with at least 5 cm overlap.
2. Mix the required quantities of Sikalastic® Rapid-722/-722 Detail.
3. Apply approx. 2/3 of the total consumption per m<sup>2</sup> Sikalastic® Rapid-722/-722 Detail as the first layer.
4. Laminate the Sikalastic® Rapid Fleece 110 Perforated wet on wet, free of bubbles and wrinkles, into the fresh Sikalastic® Rapid-722/-722 Detail. Fleece must be completely soaked and glued over the entire surface to the substrate. Fleece overlaps are carried out with at least 5 cm.
5. Apply approx. 1/3 of the total consumption per m<sup>2</sup> of Sikalastic® Rapid-722/-722 Detail as a second layer until the fleece structure is completely covered by the sealing resin.

## LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### Sika Deutschland CH AG & Co KG

Kornwestheimer Straße 103 - 107  
D - 70439 Stuttgart  
Tel.: +49 711 8009-0  
Fax: +49 711 8009-321  
info@de.sika.com  
www.sika.de

### PRODUCT DATA SHEET

Sikalastic® Rapid Fleece 110 Perforated  
January 2026, Version 01.01  
020915952000000088

SikalasticRapidFleece110Perforated-en-DE-(01-2026)-1-1.pdf