

PRODUCT DATA SHEET

Sikafloor®-80 Antislip

Anti-slip agent

DESCRIPTION

Polyethylene based additive to increase slip resistance of Sikafloor® Top Coats.

USES

- Plastic granules to increase slip resistance
- As an additive to various Sikafloor® EP and PU Top Coats

FEATURES

- Optional system component for Sikafloor® Top Coats
- Anti-scratch
- Abrasion resistant
- Matting of glossy surfaces

PRODUCT INFORMATION

Composition	Fine-grain polyethylene	
Packaging	Bucket:	5 kg
	Carton:	12 x 0,2 kg
Shelf life	In unopened original container: 12 months from production date	
Storage conditions	Store in dry conditions at temperatures between +5 °C and +30 °C	
Appearance and colour	White powder	

APPLICATION INFORMATION

Consumption	2 - 4 % in Sikafloor® Top Coats
-------------	---------------------------------

BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other

safety-related data.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Deutschland GmbH

Flooring / Waterproofing
Kornwestheimer Straße 103-107
D-70439 Stuttgart
Telefon: 0711/8009-0
E-Mail:
flooring_waterproofing@de.sika.com



PRODUCT DATA SHEET

Sikafloor®-80 Antislip
March 2024, Version 03.01
020816020010000008

Sikafloor-80Antislip-en-DE-(03-2024)-3-1.pdf

