

## DECLARATION OF PERFORMANCE

N°

02	14	01	01	100	0	000004	1017
----	----	----	----	-----	---	--------	------

1. Unique identification code of the product-type:	<b>Sigunit® 49 AF</b>
2. Type batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):	See packaging
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:	Alkali free setting accelerator for shotcrete
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):	Sika France S.A.S. 84 rue Edouard Vaillant 93350 Le Bourget <a href="http://www.sika.fr">www.sika.fr</a>
5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):	Not relevant
6. System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V:	System 2+
7. In case of the declaration of performance (DoP) concerning a construction product covered by a harmonised standard:	CERIB, notified factory production control certification body N°1164 issued the certificate of conformity of the factory production control.
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment (ETA) has been issued:	Not relevant

Declaration of Performance



## 9. Declared performance

Essential characteristics	Performances	Harmonised technical specification
Chloride ion content	≤ 0.1 %	NF EN 934-5 : 2007-12
Alkali content	≤ 0.25 %	
Effet sur la corrosion	UP***	
Initial setting time	≤ 10 min	
Final setting time	≤ 60 min	
Compressive strength after 28 days	AM* ≥ 90 % CM**	
Compressive strength after 90 days	AM* ≥ CM**after 28 days	
Compressive strength after 28 days	See safety data sheet (MSDS)	

\*AM: Mortar with admixture - \*\*CM : Control mortar - \*\*\*UP : Unmeasured performance

## 10. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

BU Manager

Alfred RECHSTEINER  
General Manager SIKA FRANCE

Paris, 13/06/2013

## Ecology, Health and Safety Information (REACH)

A material safety data sheet is established in compliance with REACH regulation, article 31. It is available on the web [www.quickfds.fr](http://www.quickfds.fr) and [www.sika.fr](http://www.sika.fr)

### Legal note:

This information is given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.