

EN 1504-2:2004

0921

DECLARATION OF PERFORMANCE Sikagard[®]-740 W

13

02 03 03 01 002 0 000048 1105

	1. Product Type: Unique identification code of the product-type:	Sikagard [®]
	2. Type batch or serial number or any other	-740 W
	element allowing identification of the construction product as required under Article 11(4):	Batch Number (refer to packaging)
	3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:	Water-repellent impregnation (hydrophobic treatment) for absorbent substrates such as concrete in civil engineering or building concrete structures.
	,	Suitable for protection against ingress (Principle 1, method 1.1 of EN 1504-9),
		Suitable for moisture control (Principle 2, method 2.1 of EN 1504-9)
		Suitable for increasing the resistivity (Principle 8, method 8.1 of EN 1504-9)
	4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):	Sikagard [®]
		Sika Services AG Tüffenwies 16 8048 Zürich Switzerland
		Factory 1105
	5. Contact Address: Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):	Not relevant (see 4)
	6. AVCP: System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:	System 2+
	7. Notified body: In case of the declaration of performance concerning a construction product covered by a harmonised standard:	0921 Notified factory production control certification body No. 0921 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control, 0921-CPD-2050 .

For Further Information:

R

Insert Local Address and Contact Numbers

Refurbishment EC Declaration of Performance Edition 02.2013 Identification no. 02 03 03 01 002 0 0000481105 Version no. 1

8. Notified body:

In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not relevant (see 7)

9. Declared performance

Essential characteristics	Performance	Test Standard	Harmonised technical specification
Depth of penetration:	Class I: <10 mm	EN 1504-2 Table 3	
Water absorption and res	sistance to alkali as:		EN 1504-2: 2004
Absorption ratio:	< 7.5% compared with the untreated specimen	EN 13580 E	
Absorption ratio:	< 10% after immersion in alkali solution		
Drying rate:	Class I: > 30%	EN 13579	
Resistance to freeze thaw salts stress:	Pass	EN 13581	



For Further Information:

R

Insert Local Address and Contact Numbers

10. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

). Gritzing fl. Rof

Jochen Grötzinger Entwicklung

Martin Rolfes Marketing

Junil

Dr. Heinz Ephardt Qualitätssicherung

Stuttgart, 1. Juli 2013

Ecology, Health and Safety Information (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

Legal note:

This information is given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

a Deutschland GmbH westheimer Str. 103-107 Stuttgart Telefon Telefax www.sika.de (07 11) 80 09-0 (07 11) 80 09-321