

ENVIRONMENTAL PRODUCT DECLARATION

as per ISO 14025 and EN 15804+A2

Owner of the Declaration	Sika Services AG
Publisher	Institut Bauen und Umwelt e.V. (IBU)
Programme holder	Institut Bauen und Umwelt e.V. (IBU)
Declaration number	EPD-SIK-20240389-CBA1-EN
Issue date	19.12.2024
Valid to	18.12.2029

Sika® ViscoCrete®-520 P
Sika Deutschland GmbH

www.ibu-epd.com | <https://epd-online.com>



ECO PLATFORM

EPD
VERIFIED



General Information

Sika Deutschland GmbH

Programme holder

IBU – Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

Declaration number

EPD-SIK-20240389-CBA1-EN

This declaration is based on the product category rules:

Concrete admixtures, 01.08.2021
(PCR checked and approved by the SVR)

Issue date

19.12.2024

Valid to

18.12.2029



Dipl.-Ing. Hans Peters
(Chairman of Institut Bauen und Umwelt e.V.)



Florian Pronold
(Managing Director Institut Bauen und Umwelt e.V.)

Sika® ViscoCrete®-520 P

Owner of the declaration

Sika Services AG
Tüffenwies 16-22
8064 Zurich
Switzerland

Declared product / declared unit

1 kg of Sika® ViscoCrete®-520 P

Scope:

This core-EPD relates to 1 kg of Sika® ViscoCrete®-520 P, a superplasticizer and water reducer in powder form, produced in Leimen, Germany and is representative for the year 2023.


The results in this core-EPD were calculated using an LCA-tool verified by IBU in 2023.

The owner of the declaration shall be liable for the underlying information and evidence; the IBU shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

The EPD was created according to the specifications of EN 15804+A2. In the following, the standard will be simplified as *EN 15804*.

Verification

The standard EN 15804 serves as the core PCR	
Independent verification of the declaration and data according to ISO 14025:2011	
<input type="checkbox"/>	internally
<input checked="" type="checkbox"/>	externally



Matthias Schulz,
(Independent verifier)

Product

Product description/Product definition

Sika® ViscoCrete®-520 P is a superplasticizer and water reducer in powder form based on Sika® ViscoCrete® polycarboxylate polymer technology.

For the placing of the product on the market in the European Union/European Free Trade Association (EU/EFTA) (with the exception of Switzerland) Regulation (EU) No. 305/2011 (CPR) applies. The product needs a declaration of performance taking into consideration EN 934-2:2009+A1:2012, Admixtures for concrete, mortar and grout - Part 2: Concrete admixtures - Definitions, requirements, conformity, marking and labelling, and the CE marking.

For the application and use the respective national provisions apply.

Application

For the production of dry-mixed mortars and concrete for applications like floor screeds, underlayments, and grouts. Solid particles are very effectively dispersed in the mix, enabling high water reduction and/or improved flowability of mortar and concrete, and related benefits like

- Portland cement clinker reduction/substitution,
- Reduced mixing, placing and compacting efforts,
- Increased density and strength,
- Reduced shrinkage, and enhanced durability.

Technical Data

Sika® ViscoCrete®-520 P meets the requirements of EN 934-2, Table 3.1/3.2.

Constructional data

Name	Value	Unit
Composition	Modified polycarboxylates	
Appearance / Colour	White powder	
Bulk Density	0.6 ± 0.1	g/cm ³
pH value (ISO 4316)	4.0 ± 0.5 at +23 °C (40 % solution)	-log ₁₀ (a _{H+})
Equivalent Sodium Oxide	≤ 2.0 (Na ₂ O-equiv.)	%
Total Chloride Ion Content	≤ 0.1	%
Recommended dosage	0.05 - 0.5	% by weight of binder

Additional technical data are not relevant for this product. Performance data of the product in accordance with the declaration of performance with respect to its essential characteristics according to EN 934-2:2009+A1:2012[MM1], Admixtures for concrete, mortar and grout - Part 2: Concrete admixtures - Definitions, requirements, conformity, marking and labelling.

Base materials/Ancillary materials

The products chemical base are modified polycarboxylates.

- This product/article/at least one partial article contains substances listed in the ECHA candidate list (date: 30.11.2023) exceeding 0.1 percentage by mass: **no**
- This product/article/at least one partial article contains other cancerogenic, mutagenic, reprotoxic (CMR) substances in categories 1A or 1B which are not on the ECHA candidate list, exceeding 0.1 percentage by mass: **no**
- Biocide products were added to this construction product or it has been treated with biocide products (this then concerns a treated product as defined by the REGULATION (EU) No 528/2012: **no**

Reference service life

A reference service life according to the ISO 15686:1, -2, -7 and -8 standards cannot be declared as the additives are fully integrated into mortar/concrete.

The durability of concrete admixtures is normally at least as long as the lifetime of the building in which they are used. Experimental data show that the reference life is greater than 50 years. Documentation of the RSL is not required for the EPDs calculated using the EPD tool from Sika since the entire life cycle is not declared. Only modules A1-A3, A4, A5, C1-C4 and D are considered.

LCA: Calculation rules

Declared Unit

The EPD refers to the declared unit of 1 kg of concrete admixture (superplasticizer) powder applied into the building in accordance with IBU PCR 04-2023 part B for concrete admixtures. The max. permissible dosage of Sika® ViscoCrete®-520 P is 0.5 mass % by weight of binder.

Declared unit and mass reference

Name	Value	Unit
Declared unit	1	kg
Gross density	0.6	kg/dm ³
Bulk Density	0.6 ± 0.1	g/cm ³

System boundary

Declaration type with respect to life cycle stages covered according to clause 5.2 EN 15804+A2 is cradle to gate with modules C1-C4 and module D (A1-A3, A4, A5, C and D). Modules taken into account:

- A1 Production of preliminary products
- A2 Transport to the plant
- A3 Production including provision of energy, production of auxiliaries and consumables and waste treatment
- A4 Transport from the construction site to the installation site
- A5 Installation, admixtures applied into the building during A5 phase operations. At this stage, an impact of the production and treatment of installation residue equal to 1% of the product is considered.
- C1-C2-C4-D

The building deconstruction (demolition process) takes place in the C1 module which considers energy production and consumption in terms of diesel and all the emissions connected with the fuel-burning process. After the demolition, the admixture is transported to the end-of-life processing (C2 module) where all the impacts related to the transport processes are considered.

One scenario is considered for the final treatment of the waste:

- 100% disposal (C4), modelled by landfill process where admixtures end their life cycle.

Module D accounts for benefits that are beyond the defined system boundaries. Credits are generated during the incineration of the installation scrap in module A5.

Geographic Representativeness

Land or region, in which the declared product system is manufactured, used or handled at the end of the product's lifespan: Germany

Comparability

Basically, a comparison or an evaluation of EPD data is only possible if all the data sets to be compared were created according to *EN 15804* and the building context, respectively the product-specific characteristics of performance, are taken into account. Sphera LCA for Expert software (version 10) and Managed LCA Content (2022.2) have been used.

LCA: Scenarios and additional technical information

Characteristic product properties of biogenic carbon

No biogenic carbon is contained in the product or in the packaging.

Information on describing the biogenic carbon content at factory gate

Name	Value	Unit
Biogenic carbon content in product	-	kg C
Biogenic carbon content in accompanying packaging	-	kg C

Note: 1 kg of biogenic carbon is equivalent to 44/12 kg of CO₂.

Transport from the gate to the site (A4)

Name	Value	Unit
Transport distance Truck	563	km
Transport distance Train	946	km
Transport distance Ship	25	km

Assembly (A5)

Name	Value	Unit
Material loss	0.01	kg

Material loss regards the amount of product not used during the application phase into the building. This amount is 1 % of the product, impacts related to the production of this part are charged to the A5 module. This percentage is considered as waste to incineration since the product has a calorific value and impacts of its end of life have been considered in the LCA model and declared in A5.

A reference service life according to the ISO 15686:1, -2, -7 and -8 standards cannot be declared as the additives are fully integrated into mortar/concrete. Their service life thus depends on the service life of the concrete structure they are used in.

End of life (C1-C4)

C1: This module considers the use of machinery (7.5E-5 kg of diesel for kg handled) to dismantle the product to enable its subsequent transport.

C2: The concrete demolition waste is transported from the building site to a treatment plant or disposal site by truck and an average distance of 50 km is considered.

C3: Waste processing. No waste processing is considered.

C4: The results for the end-of-life are declared for one scenario:

Name	Value	Unit
Landfill percentage	100	%
Material to landfill	1	kg

LCA: Results

DESCRIPTION OF THE SYSTEM BOUNDARY (X = INCLUDED IN LCA; MND = MODULE OR INDICATOR NOT DECLARED; MNR = MODULE NOT RELEVANT)

Product stage			Construction process stage		Use stage							End of life stage				Benefits and loads beyond the system boundaries
Raw material supply	Transport	Manufacturing	Transport from the gate to the site	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	X	X	MND	MND	MNR	MNR	MNR	MND	MND	X	X	X	X	X

RESULTS OF THE LCA - ENVIRONMENTAL IMPACT according to EN 15804+A2: 1 kg Sika® ViscoCrete®-520 P

Parameter	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
GWP-total	kg CO ₂ eq	2.74E+00	3.83E-02	7.24E-02	2.83E-04	6.27E-03	0	1.45E-02	-2.2E-02
GWP-fossil	kg CO ₂ eq	2.72E+00	3.7E-02	6.71E-02	2.7E-04	6E-03	0	1.49E-02	-2.18E-02
GWP-biogenic	kg CO ₂ eq	1.38E-02	1.34E-03	5.21E-03	1.23E-05	2.71E-04	0	-4.42E-04	-1.11E-04
GWP-luluc	kg CO ₂ eq	2.17E-04	1.81E-06	3.85E-06	1.25E-08	2.72E-07	0	2.75E-05	-2.38E-06
ODP	kg CFC11 eq	5.29E-12	7.33E-14	4.43E-14	2.82E-17	6.15E-16	0	3.51E-14	-1.46E-13
AP	mol H ⁺ eq	5.13E-03	1.21E-04	2.67E-04	3.62E-06	1.91E-05	0	1.06E-04	-2.85E-05
EP-freshwater	kg P eq	1.31E-05	1.02E-08	1.4E-08	6.41E-11	1.4E-09	0	2.53E-08	-2.97E-08
EP-marine	kg N eq	1.74E-03	5.31E-05	3.23E-05	1.65E-06	8.89E-06	0	2.71E-05	-7.76E-06
EP-terrestrial	mol N eq	1.99E-02	5.83E-04	4.3E-04	1.81E-05	9.78E-05	0	2.97E-04	-8.32E-05
POCP	kg NMVOC eq	5.58E-03	1.21E-04	1.11E-04	4.95E-06	1.77E-05	0	8.22E-05	-2.17E-05
ADPE	kg Sb eq	1.13E-06	2.41E-09	2.65E-09	1.44E-11	3.14E-10	0	1.53E-09	-3.27E-09
ADPF	MJ	7E+01	5.69E-01	5.83E-01	3.84E-03	8.39E-02	0	1.95E-01	-3.71E-01
WDP	m ³ world eq deprived	7.57E-01	6.12E-04	9.81E-03	7.43E-07	1.62E-05	0	1.64E-03	-2.3E-03

GWP = Global warming potential; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential of land and water; EP = Eutrophication potential; POCP = Formation potential of tropospheric ozone photochemical oxidants; ADPE = Abiotic depletion potential for non-fossil resources; ADPF = Abiotic depletion potential for fossil resources; WDP = Water (user) deprivation potential)

RESULTS OF THE LCA - INDICATORS TO DESCRIBE RESOURCE USE according to EN 15804+A2: 1 kg Sika® ViscoCrete®-520 P

Parameter	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
PERE	MJ	3.74E+00	2.43E-02	2.94E-02	2.33E-05	5.08E-04	0	2.93E-02	-1.01E-01
PERM	MJ	0	0	0	0	0	0	0	0
PERT	MJ	3.74E+00	2.43E-02	2.94E-02	2.33E-05	5.08E-04	0	2.93E-02	-1.01E-01
PENRE	MJ	6.56E+01	5.71E-01	1.13E+00	3.86E-03	8.42E-02	0	1.96E-01	-3.71E-01
PENRM	MJ	5.37E+00	0	-5.47E-01	0	0	0	0	0
PENRT	MJ	7.1E+01	5.71E-01	5.83E-01	3.86E-03	8.42E-02	0	1.96E-01	-3.71E-01
SM	kg	0	0	0	0	0	0	0	0
RSF	MJ	0	0	0	0	0	0	0	0
NRSF	MJ	0	0	0	0	0	0	0	0
FW	m ³	2.29E-02	3.65E-05	2.39E-04	3.16E-08	6.9E-07	0	4.97E-05	-9.69E-05

PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water

RESULTS OF THE LCA - WASTE CATEGORIES AND OUTPUT FLOWS according to EN 15804+A2: 1 kg Sika® ViscoCrete®-520 P

Parameter	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
HWD	kg	4.42E-09	1.22E-11	2.26E-11	1.33E-14	2.91E-13	0	1.01E-11	-5.05E-11
NHWD	kg	5.86E-02	7.49E-05	1.43E-03	3.94E-07	8.6E-06	0	1E+00	-1.87E-04
RWD	kg	1.38E-03	2.58E-05	6.74E-06	6.36E-09	1.39E-07	0	2.18E-06	-2.89E-05
CRU	kg	0	0	0	0	0	0	0	0
MFR	kg	0	0	0	0	0	0	0	0
MER	kg	0	0	0	0	0	0	0	0
EEE	MJ	0	0	9.7E-02	0	0	0	0	0
EET	MJ	0	0	1.79E-01	0	0	0	0	0

HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed; CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported electrical energy; EET = Exported thermal energy

**RESULTS OF THE LCA – additional impact categories according to EN 15804+A2-optional:
1 kg Sika® ViscoCrete®-520 P**

Parameter	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
PM	Disease incidence	4.51E-08	9.22E-10	2.09E-09	1.93E-10	1.06E-10	0	1.3E-09	-2.36E-10
IR	kBq U235 eq	1.6E-01	3.77E-03	8.39E-04	9.55E-07	2.08E-05	0	2.42E-04	-4.89E-03
ETP-fw	CTUe	2.54E+01	3.44E-01	4.72E-01	2.74E-03	5.97E-02	0	1.1E-01	-8.06E-02
HTP-c	CTUh	1.06E-09	6.39E-12	1.13E-11	5.09E-14	1.11E-12	0	1.67E-11	-3.73E-12
HTP-nc	CTUh	7.67E-08	3.2E-10	3.46E-10	3.52E-12	5.51E-11	0	1.85E-09	-1.44E-10
SQP	SQP	2.26E+00	1.63E-02	1.7E-02	2.28E-05	4.98E-04	0	4.07E-02	-6.54E-02

PM = Potential incidence of disease due to PM emissions; IR = Potential Human exposure efficiency relative to U235; ETP-fw = Potential comparative Toxic Unit for ecosystems; HTP-c = Potential comparative Toxic Unit for humans (cancerogenic); HTP-nc = Potential comparative Toxic Unit for humans (not cancerogenic); SQP = Potential soil quality index

Disclaimer 1 – for the indicator 'Potential Human exposure efficiency relative to U235'. This impact category deals mainly with the eventual impact of low-dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure or radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, radon and from some construction materials is also not measured by this indicator.

Disclaimer 2 – for the indicators 'abiotic depletion potential for non-fossil resources', 'abiotic depletion potential for fossil resources', 'water (user) deprivation potential, deprivation-weighted water consumption', 'potential comparative toxic unit for ecosystems', 'potential comparative toxic unit for humans – cancerogenic', 'Potential comparative toxic unit for humans - not cancerogenic', 'potential soil quality index'. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high as there is limited experience with the indicator. This EPD was created using a software tool.

References

Standards

EN 15804

EN 15804:2012+A1 2013, Sustainability of construction works — Environmental Product Declarations — Core rules for the product category of construction products.

EN 15804

EN 15804:2012+A2:2019+AC:2021, Sustainability of construction works — Environmental Product Declarations — Core rules for the product category of construction products.

ISO 14025

EN ISO 14025:2011, Environmental labels and declarations — Type III environmental declarations — Principles and procedures.

Further References

Title of the software/database

Title of the software/database. Addition to the title, version. Place: Publisher, Date of publication [Access on access date].

IBU 2021

Institut Bauen und Umwelt e.V.: General Instructions for the EPD programme of Institut Bauen und Umwelt e.V., Version 2.0, Berlin: Institut Bauen und Umwelt e.V., 2021
www.ibu-epd.com

LCA Calculator

LCA Calculator software (version 6). Visualize, Improve and Report on Product Sustainability. [https://sphaera.com/your-path\[1\]to-sustainability/](https://sphaera.com/your-path[1]to-sustainability/)

LCA for Expert

Life cycle assessment software (version 10), by SpheraSolutions GmbH, Leinfelden-Echterdingen, 2022<https://sphaera.com/life-cycle-assessment-lca-software/>

Managed LCA Content

Life cycle assessment database, by Sphera Solutions GmbH, Leinfelden-Echterdingen, 2022<https://sphaera.com/life-cycle-assessment-lca-database/>

PCR Part A

PCR - Part A: Calculation rules for the Life Cycle Assessment and Requirements on the Background Report, version 1.3, Institut Bauen und Umwelt e.V., 08-2021.

PCR Part B

PCR – Part B: Requirements on the EPD for Concrete admixtures, Institut Bauen und Umwelt e.V., 04-2023.

EN 480-10

Admixtures for concrete, mortar and grout. Test methods. Determination of water-soluble chloride content.

EN 934-2:2009+A1:2012

Admixtures for concrete, mortar and grout - Part 2

ISO 15686:1, -2, -7 and -8

Buildings and constructed assets - Service life planning: Part 1, General principles and framework
Buildings and constructed assets - Service life planning: Part 2, Service life prediction procedures
Buildings and constructed assets - Service life planning: Part 7, Performance evaluation for feedback of service life data from practice
Buildings and constructed assets - Service life planning: Part 8, Reference service life and service-life estimation



Publisher

Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

+49 (0)30 3087748- 0
info@ibu-epd.com
www.ibu-epd.com



Programme holder

Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

+49 (0)30 3087748- 0
info@ibu-epd.com
www.ibu-epd.com



Author of the Life Cycle Assessment

Sika Technology AG
Tüffenwies 16
8048 Zürich
Switzerland

+41 (0)58 436 40 40
product.sustainability@ch.sika.com
www.sika.com/sustainability



Owner of the Declaration

Sika Services AG
Tüffenwies 16-22
8064 Zurich
Switzerland

+41(0)58 436 40 40
avdyli.elma@ch.sika.com
<https://www.sika.com/>