

## PRODUCT DATA SHEET

# SikaForce®-096 Cleaner

(formerly SikaForce®-7260 Cleaner)

Cleaning liquid for tools and application equipment

**TYPICAL PRODUCT DATA (FURTHER VALUES SEE SAFETY DATA SHEET)**

<b>Chemical base</b>	Dipropylene glycol ether
<b>Density</b>	0.97 g/cm <sup>3</sup>
<b>Viscosity</b>	Z3 DIN, shear rate 50 s <sup>-1</sup> 3.5 mPa·s <sup>A</sup>
<b>Vapor pressure</b>	0.4 mm Hg/25 °C
<b>Boiling point</b>	190 °C
<b>Flash point</b>	79 °C
<b>Shelf life</b>	12 months

CQP = Corporate Quality Procedure

A) 23 °C / 50 % r.h.

**DESCRIPTION**

SikaForce®-096 Cleaner is a liquid with high boiling point for removing of non-cured 1- and 2-component polyurethane products from tools and application equipment.

**PRODUCT BENEFITS**

- Not classified
- Safe to use
- Neutralizes the isocyanate groups in polyurethane products

**AREAS OF APPLICATION**

SikaForce®-096 Cleaner is used for cleaning of tools and flushing of application equipment after dispensing SikaForce adhesives. This product is suitable for experienced professional users only.

## METHOD OF APPLICATION

Only uncured 1- and 2-component polyurethane products can be removed with SikaForce®-096 Cleaner.

Provide adequate ventilation. If SikaForce®-096 Cleaner is processed at temperatures > 30 °C use a local extraction system.

Clean tools by using a brush. If necessary, immerse parts in the SikaForce®-096 Cleaner prior the cleaning process.

For 2-component equipment, it is recommended flushing with recirculation.

## STORAGE CONDITIONS

SikaForce®-096 Cleaner has to be kept between 10 °C and 30 °C in a tightly closed packaging and stored in a well-ventilated storage room.

Minimum temperature during transportation is -20 °C for max. 7 days.

## FURTHER INFORMATION

The information herein is offered for general guidance only. Advice on specific applications is available on request from the Technical Department of Sika Industry.

Copies of the following publications are available on request:

- Safety Data Sheets

## BASIS OF PRODUCT DATA

All technical data stated in this document are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## HEALTH AND SAFETY INFORMATION

For information and advice regarding transportation, handling, storage and disposal of chemical products, users shall refer to the actual Safety Data Sheets containing physical, ecological, toxicological and other safety-related data.

## DISCLAIMER

The information, and, in particular, the recommendations relating to the application and enduse of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

## PRODUCT DATA SHEET

SikaForce®-096 Cleaner  
Version 02.01 (03 - 2021), en\_DE  
019404010960001000

## Sika Deutschland GmbH

Industry  
Stuttgarter Straße 139  
72574 Bad Urach  
Tel. +49 7125 940-7692  
verkauf.industry@de.sika.com  
www.sika.de

