

## PRODUCT DATA SHEET

# SikaShield® Titanol E

Solvent-free, water-dilutable bitumen emulsion as primer

### DESCRIPTION

SikaShield® Titanol E is a solvent-free, water-dilutable bitumen emulsion.

### USES

Bitumen primer (emulsion) for exterior and interior use

- Adhesion primer for bitumen waterproofing membranes on all mineral, absorbent substrates (e.g. concrete and cement surfaces)

### FEATURES

- Good adhesion
- Ecologically harmless
- Odorless
- Chemically well tolerated

### SUSTAINABILITY

Giscode: BBP 10

### PRODUCT INFORMATION

|                    |   |       |
|--------------------|---|-------|
| Composition        | Water-bitumen emulsion  |       |
| Packaging          | 25 l bucket   |       |
| Colour             | dry:  | black |
|                    | wet:  | brown |
| Shelf life         | 24 months if stored properly  |       |
| Storage conditions | Store in the original sealed container under dry and cool conditions. |       |
| Density            | Approx. 1 kg/dm <sup>3</sup>  |       |

### APPLICATION INFORMATION

|                         |   |
|-------------------------|---|
| Consumption             | 0.3 to 0.4 l/m <sup>2</sup>   |
| Ambient air temperature | We recommend a minimum temperature of +5 °C during the application. |
| Substrate temperature   | We recommend a minimum temperature of +5 °C during the application. |
| Substrates              | Also suitable in damp, but not wet weather                          |

## Drying time

Approx. 30 hours  
This information applies to temperatures > +20 °C.

Depending on the temperature, environmental conditions of the substrate and the amount of primer applied.

## BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## ECOLOGY, HEALTH AND SAFETY

### REGULATION (EC) NO 1907/2006 - REACH

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

## APPLICATION INSTRUCTIONS

### General provisions on substrate quality:

The substrate must be uniform, firm, smooth and free of any sharp protrusion or burrs, clean, dry, free of grease, oil, dust and loosely adhering particles.

### Substrate preparation:

Use the appropriate preparation equipment to achieve the required substrate quality.

### General provisions for the application:

Strictly follow installation procedures as defined in method statement, application manuals and working instructions which must always be adjusted to the actual site conditions. All corresponding processing standards and regulations must be obeyed.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

**Sika Deutschland CH AG & Co KG**  
Kornwestheimer Straße 103 - 107  
D - 70439 Stuttgart  
Tel.: +49 711 8009-0  
Fax: +49 711 8009-321  
info@de.sika.com  
www.sika.de

**PRODUCT DATA SHEET**  
SikaShield® Titanol E  
April 2026, Version 02.01  
02094507510000010

SikaShieldTitanolE-en-DE-(04-2026)-2-1.pdf