

PRODUCT DATA SHEET

Sikalastic® Fleece-200

Polyester fleece reinforcement for Sikalastic® liquid applied membrane systems

DESCRIPTION

Sikalastic® Fleece-200 is a polyester fleece used for reinforcing Sikalastic® Liquid Applied Membrane systems.

USES

- Reinforcement for Sikalastic® 641 Systems

FEATURES

- Ensures the correct thickness of the system
- Improves the crack-bridging properties of the system
- Improves the mechanical properties of the system

CERTIFICATES AND TEST REPORTS

- CE Marking and Declaration of Performance to European Technical Assessment ETA 14/0177

PRODUCT INFORMATION

Composition	100 % Polyester	
Packaging	Rolls	
	Roll width	Roll length
	0.2 m	50 m
	0.3 m	50 m
	1,05 m	50 m
	Refer to current price list for packaging variations.	
Appearance and colour	white	
Shelf life	If stored properly the product retains its properties.	
Storage conditions	Store in original, unopened and undamaged sealed packaging under dry conditions at temperatures between +5 °C and +35 °C. Always refer to packaging.	
Max. operating pressure	200 g/m ²	

TECHNICAL INFORMATION

Tensile strength	~200 N/5 cm
------------------	-------------

APPLICATION INFORMATION

Ambient air temperature	Refer to the Product Data Sheet of the Sika® Liquid Applied Membrane
Substrate temperature	Refer to the Product Data Sheet of the Sika® Liquid Applied Membrane

SYSTEM INFORMATION

System structure

For detailed information regarding system build-up, refer to the Sikalastic® Premium Fleece System or Product Data Sheet of the Sika® Liquid Applied Membrane.

BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

APPLICATION INSTRUCTIONS

APPLICATION

Reference must be made to the Sika® Method Statement of the corresponding Liquid Applied Membrane system for full application details.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Deutschland CH AG & Co KG
Kornwestheimer Straße 103 - 107
D - 70439 Stuttgart
Tel.: +49 711 8009-0
Fax: +49 711 8009-321
info@de.sika.com
www.sika.de

PRODUCT DATA SHEET
Sikalastic® Fleece-200
April 2026, Version 03.01
020915952000000001

SikalasticFleece-200-en-DE-(04-2026)-3-1.pdf