

PRODUCT DATA SHEET

Hydrotite SS Profiles

Hydrophilic swellable joint sealing profiles

DESCRIPTION

Hydrotite SS Profiles is a hydrophilic swellable joint sealing profile on polychloroprene basis (CR=chloroprene rubber, neoprene). It swells in contact with water to seal all types of construction joints in pipe penetrations.

USES

Joint sealing:

- Pipe and steel work penetrations through walls and floor slabs
- Around all types of penetrations and connection joints

FEATURES

- Comprised of modified chloroprene rubber
- Special expansion delay coating to allow concrete cure prior to expansion
- Reliable and durable
- Simple, low cost installation
- Available in different sizes
- Can withstand high hydrostatic pressures

CERTIFICATES AND TEST REPORTS

General Building Authority Test Certificate for HYDROTITE water-expanding rubber profile; MFPA Leipzig 2006

Swelling behavior of HYDROTITE in contact with fluids with different pH-values; MFPA Leipzig 2006

Resistance test of HYDROTITE to sewage, liquid manure and silage effluent; MFPA Leipzig 2006

Determination of the effects of liquids according to DIN ISO 1817 with various de-icing agents and kerosine; MFPA Leipzig 2008

PRODUCT INFORMATION

Packaging	Profile	Packaging
	SS-0220	Card Box with 4 Rolls x 25 m
	SS-0420	Card Box with 4 Rolls x 20 m
Appearance and colour	hydrophilic blue coloured profile on polychloroprene basis (CR=chloroprene rubber, neoprene)	
Shelf life	24 months from the date of production in unopened original packaging and correct storage conditions	
Storage conditions	The product must be stored in original, unopened and undamaged packaging in dry conditions at temperatures between +5 °C and +35 °C. Always refer to packaging.	

Dimensions	Profile	Dimensions
	SS-0220	2 x 20 mm
	SS-0420	4 x 20 mm
<hr/>		
Ambient air temperature	depending on the application method, please refer to the data sheet of the corresponding adhesive	
<hr/>		
Substrate temperature	depending on the application method, please refer to the data sheet of the corresponding adhesive	

SYSTEM INFORMATION

System structure	recommended adhesive for application: Sikadur®-82 WB
------------------	---

BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY

The substrate must be sound, clean, dry or matt damp, free from all surface contaminants that could impair the adhesion.

APPLICATION

IMPORTANT

Concrete cover

Insufficient concrete cover, low density concrete or voids will prevent the Hydrotite SS Profiles from developing its waterproofing function.

1. Place the Hydrotite SS Profiles in the centre of the concrete structure.
2. In concrete maintain a minimum cover of 8 cm on both sides.

SEALANT WITH Hydrotite SS Profiles:

1. Apply adhesive in a narrow bed (size of triangular section ~12 mm tall and ~12 mm wide) onto the prepared substrate. Extrude enough material to level the roughness of the substrate.
2. Place and press the Hydrotite SS Profiles firmly into the fresh applied adhesive.
3. Ensure full and continuous contact between the adhesive and both the Hydrotite SS Profiles and the substrate is achieved.
4. Protect the Hydrotite SS Profiles against water (for example, rain) until the concrete is placed. The application of Hydrotite SS Profiles should be carried out in dry weather conditions if possible or shortly before concreting. Due to the factory-applied delay coating it is possible to expose the product unprotected to wet weather conditions for maximum 2 to 3 days.

5. During placement compact the fresh concrete well around the Hydrotite SS Profiles to achieve dense concrete without any honeycombing or voids.



PRODUCT DATA SHEET

Hydrotite SS Profiles

March 2025, Version 01.01

020703300200000007

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

HydrotiteSSProfiles-en-DE-(03-2025)-1-1.pdf