

## PRODUCT DATA SHEET

# Sarnatape<sup>®</sup>-20

Butyl rubber adhesive tape

### DESCRIPTION

Sarnatape<sup>®</sup>-20 is a butyl rubber, double-sided adhesion sealing tape with a controlled stretch range.

### USES

Sarnatape<sup>®</sup>-20 may only be used by experienced professionals.

- Applied at airtight level for taping of seams, connections, terminations and detailing of Sarnavap<sup>®</sup> vapour control layers (polyethylene).

### FEATURES

- Finger-lift release liner
- Controlled adhesive stretch range
- Good adhesion



### PRODUCT INFORMATION

<b>Composition</b>	Adhesive	Butyl rubber
	Release liner	Polypropylene
<b>Packaging</b>	10 rolls in a box.	
<b>Appearance and colour</b>	Smooth flat profile. Adhesive: Anthracite	
<b>Shelf life</b>	2 years from date of production	
<b>Storage conditions</b>	The product must be stored in original, unopened and undamaged sealed packaging in dry conditions at temperatures between +5 °C and +25 °C. Always refer to packaging.	
<b>Density</b>	1,2 g/cm <sup>3</sup> (+20 °C)	
<b>Length</b>	20,00 m (-4 cm / +10 cm)	
<b>Width</b>	20 mm (+/- 1,0 mm)	
<b>Thickness</b>	1,50 mm (-0 mm / +0,2 mm)	

## APPLICATION INFORMATION

Ambient air temperature min. +5 °C / max. +40 °C

Substrate temperature min. +5 °C / max. +40 °C

## SYSTEM INFORMATION

### System structure

Compatible system products:  
▪ Sarnavap® PE vapour control layers  
Ancillary products:  
▪ Primer 130

### Compatibility

Not compatible in direct contact with PVC, tar, asphalt, hot bitumen, wood preservatives with surfactants and substances containing oil, solvents or wetting agents. These materials could adversely affect the product properties.

## BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## IMPORTANT CONSIDERATIONS

- The use of Sarnatape®-20 is limited to geographical locations with average monthly minimum temperatures of -30 °C. Permanent ambient temperature during use is limited to +50 °C.
- Stress-free bonding is required
- Do not use if exposed to permanent UV
- Do not use for bonding if subjected to mechanical loading

## ECOLOGY, HEALTH AND SAFETY

### REGULATION (EC) NO 1907/2006 - REACH

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

Sika Deutschland CH AG & Co KG  
Kornwestheimer Straße 103 - 107  
D - 70439 Stuttgart  
Tel.: +49 711 8009-0  
Fax: +49 711 8009-321  
info@de.sika.com  
www.sika.de

## APPLICATION INSTRUCTIONS

### SUBSTRATE QUALITY

The contact surfaces must be secure, dry, clean and free of all contaminants such as dust, grease and other materials which could affect adhesion.

### SUBSTRATE PREPARATION

Porous contact surfaces must first be primed with Primer 130 (refer to Product Data Sheet) before application of the tape.

## LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sarnatape-20-en-DE-(04-2026)-1-2.pdf

### PRODUCT DATA SHEET

Sarnatape®-20  
April 2026, Version 01.02  
02094505120000004