

## PRODUCT DATA SHEET

# Sika ViscoFlow<sup>®</sup>-30

## SUPERPLASTISIZER FOR READY-MIX CONCRETE

### DESCRIPTION

Sika ViscoFlow<sup>®</sup>-30 is a PCE-based superplasticizer for ready-mixed concrete.

### USES

- Production of ready-mix concrete
- Suitable for most concrete types

### FEATURES

- Strong water reduction
- Ideal slump-life
- Suitable for many applications

### CERTIFICATES AND TEST REPORTS

EN 934-2:T2, T3.1, T3.2  
Plastisizer and superplastisizer  
for the production of concrete  
Complies with the requirements of the ZTV-ING

### PRODUCT INFORMATION

Composition	Polycarboxylate ether
Packaging	Drum: 200 kg Container: 1000 kg Bulk: > 6 t
Appearance and colour	Fluid / Light-Yellow
Shelf life	Minimum of 1 year shelf life in sealed containers. Mix before using after longer storage times.
Storage conditions	Protect against frost, strong sunlight and contamination. Utilise clean tanks and containers when delivered in bulk.
Density	1.04 g/cm <sup>3</sup> at 20°C
pH-Value	approx. 5
Total chloride ion content	< 0.10 %
Equivalent sodium oxide	< 0.5 %

## APPLICATION INFORMATION

### Recommended dosage

0.2 - 2.5 % bwoc

Initial test according to DIN EN 206-1/DIN 1045-2 is required.

## BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

## LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### Sika Deutschland CH AG & Co KG

Kornwestheimer Straße 103 - 107

D - 70439 Stuttgart

Tel.: +49 711 8009-0

Fax: +49 711 8009-321

info@de.sika.com

www.sika.de

### PRODUCT DATA SHEET

Sika ViscoFlow®-30

October 2025, Version 01.01

021301011000001070

SikaViscoFlow-30-en-DE-(10-2025)-1-1.pdf