

## PRODUCT DATA SHEET

# Sikalastic® Rapid TPO/FPO Primer

Primer for FPO- waterproofing membranes in the Sikalastic® Rapid-722 system

## DESCRIPTION

Sikalastic® Rapid TPO/FPO Primer is a one-component, solvent-based primer.

## USES

Sikalastic® Rapid TPO/FPO Primer may only be used by experienced professionals.

Primer for the bond between Sikalastic®-722/-722 Detail and e.g. Sarnafil® FPO single-ply membranes (based on PP) for use in roofing areas and for detailing.

## FEATURES

- Fast drying
- Quick and easy application
- Low consumption

## PRODUCT INFORMATION

<b>Packaging</b>	Metal packaging	0.8 kg
<b>Shelf life</b>	12 month from production date. The expiration date is displayed on the product.	
<b>Storage conditions</b>	Dry storage in unopened and undamaged original packaging between +5 °C und +30 °C.	
<b>Density</b>	0.91 g/m <sup>3</sup>	
<b>Yield</b>	Singular material application with approx. 0.05 kg/m <sup>2</sup>	
<b>Ambient air temperature</b>	min. +5 °C / max. +35 °C	
<b>Relative air humidity</b>	≤ 90 %	
<b>Substrate temperature</b>	min. +5 °C / max. +35 °C	

## Waiting time to overcoating

Before applying the Sikalastic®-722/-722 Detail system to the Sikalastic® Rapid TPO/FPO Primer, the following waiting times must be observed:

substrate temperature	min. waiting time	max. waiting time
+23 °C	approx. 30 minutes	6 h
50 % rel. humidity		
+5 °C	approx. 60 minutes	6 h
50 % rel. humidity		

## BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

## APPLICATION INSTRUCTIONS

### SUBSTRATE PREPARATION

The surface of the FPO membranes must be clean, dry, free of oil, grease, salts, silicones and other substances that reduce adhesion. All surfaces must be cleaned with Sikalastic® Rapid Cleaner. The Sikalastic® Rapid Cleaner must be allowed to evaporate for at least 15 minutes.

The reference substrate is Sarnafil® FPO singleply waterproofing membranes based on PP. For other FPO membranes (based on PP), local adhesion tests are required in consultation with Sika® Application Technology.

## APPLICATION

Sikalastic® Rapid TPO/FPO Primer is applied to the cleaned surface in one coat. Ensure that the primer covers the substrate completely and in an even layer thickness.

Shake the container for approx. 2 minutes before use. Close the container tightly immediately after use.

Wear suitable protective equipment during use. Ensure adequate ventilation when using in closed rooms.

The primer surface must be tack-free before applying the Sikalastic®-722/-722 Detail System.

Use solvent-resistant brushes or rollers.

## LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### Sika Deutschland CH AG & Co KG

Roofing  
Kornwestheimer Strasse 103-107  
70439 Stuttgart  
Tel.: +49 711 8009-0  
roofing@de.sika.com  
www.sika.de/dachabdichtung



### PRODUCT DATA SHEET

Sikalastic® Rapid TPO/FPO Primer  
February 2025, Version 01.01  
02091540200000013

SikalasticRapidTPOFPOPrimer-en-DE-(02-2025)-1-1.pdf

