

PRODUCT DATA SHEET

Sikalastic® Rapid KAT powder

Catalyst powder for Sikalastic® Rapid products based on PMMA

DESCRIPTION

Catalyst powder for the Sikalastic® Rapid -722 sealing resins and system primer based on PMMA.

USES

Required component as a process starter and adjustment of the temperature-dependent hardening reactions of the PMMA-based Sikalastic® Rapid products.

CHARACTERISTICS / ADVANTAGES

- good solubility
- highly efficient
- flammable

PRODUCT INFORMATION

Composition	Peroxide powder	
Packaging	Accessory pack:	0,1 kg bag
	Merchandise:	2 x 0,1 kg bag
Colour	White powder	
Shelf life	12 months from the date of production in the unopened, undamaged original container. The production date is indicated on each packaging.	
Storage conditions	Store cool, dry and protected from direct sunlight in undamaged original packaging < +25°C. Sikalastic® Rapid KAT powder is highly flammable. Do not expose to direct sunlight and/or sources of heat or ignition. The effect of heat reduces the effectiveness of the product. Observe further information on storage and transport in the safety data sheet.	
Density	1,23 g/cm ³ Bulk density: 0,65 g/cm ³	

APPLICATION INFORMATION

Mixing ratio	The required amount Sikalastic® Rapid KAT powder depending on the ambient temperature can be found on the label or product data sheet of the product used.
---------------------	--

BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

FURTHER INFORMATION

The efficiency of the Sikalastic® Rapid KAT powder is reduced by the effects of heat and extreme frost.

ECOLOGY, HEALTH AND SAFETY

Before processing the products, the user must read the associated, current safety data sheets (SDS). The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

APPLICATION

Sikalastic® Rapid KAT powder is slowly added to the PMMA-based Sikalastic® Rapid products with the mixer running and mixed for at least 5 minutes until a homogeneous resin is obtained. Further information on the dosage quantities can be found in the respective product data sheets for the PMMA-based Sikalastic® Rapid products.

LOCAL RESTRICTIONS

The information in this product data sheet is valid for the product supplied by Sika Deutschland GmbH. Please note that information in other countries may differ. Please note the product data sheet valid abroad.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

In addition, our respective terms of sale, delivery and payment apply, which can be viewed and downloaded from www.sika.de. The latest product data sheet applies, which can be requested from us or downloaded from the Internet at www.sika.de.