

## PRODUCT DATA SHEET

# Sarnafil® T Pipe Flashing

Prefabricated FPO pipe/vent flashing

### DESCRIPTION

Sarnafil® T Pipe Flashing is made of synthetic roof waterproofing membrane based on flexible polyolefins (FPO).

### USES

Sarnafil® T Pipe Flashing is used as a prefabricated part for pipe/vent flashing on Sarnafil® flat roof systems.

### CHARACTERISTICS / ADVANTAGES

- Resistant to permanent UV irradiation
- Easy and safe application
- Hot air welding without use of open flame



### APPROVALS / CERTIFICATES

- Reaction to fire according to DIN EN 13501-1, class E

### PRODUCT INFORMATION

<b>Composition</b>	Flexible polyolefins (FPO) based on polypropylene (PP)	
<b>Packaging</b>	Depending on the order quantity and product size, the products are packaged on pallets or in cartons	
<b>Shelf life</b>	If stored under proper conditions, the product keeps its performance.	
<b>Storage conditions</b>	Sarnafil® T Pipe Flashing must be stored between +5 °C and +30 °C protected from direct sunlight, rain and snow.	
<b>Appearance and colour</b>	<b>Colour:</b>	Beige Grey (nearest RAL 7040) Other colours on request
<b>Surface</b>	Smooth	

## Dimensions

Art. No.	Colour	Inside diameter	Sleeve height	Flange size
110461	beige	82 mm	400 mm	300 × 300 mm
135689	RAL 7040	82 mm	400 mm	300 × 300 mm
110462	beige	92 mm	400 mm	300 × 300 mm
135692	RAL 7040	92 mm	400 mm	300 × 300 mm
110456	beige	102 mm	400 mm	300 × 300 mm
135693	RAL 7040	102 mm	400 mm	300 × 300 mm
110457	beige	112 mm	400 mm	300 × 300 mm
125517	RAL 7040	112 mm	400 mm	300 × 300 mm
110458	beige	127 mm	400 mm	300 × 300 mm
135695	RAL 7040	127 mm	400 mm	300 × 300 mm
110459	beige	142 mm	400 mm	300 × 300 mm
135696	RAL 7040	142 mm	400 mm	300 × 300 mm
110460	beige	167 mm	400 mm	300 × 300 mm
135462	RAL 7040	167 mm	400 mm	300 × 300 mm

Other diameters on request.

Thickness 1.5 mm

## SYSTEM INFORMATION

System structure Compatible products: Sarnafil® AT-types  
Sarnafil® TG 66/76-types  
Sarnafil® TS 77-types

## APPLICATION INFORMATION

Ambient air temperature -20 °C min. / +60 °C max.

Substrate temperature -30 °C min. / +60 °C max.

## BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## ECOLOGY, HEALTH AND SAFETY

### REGULATION (EC) NO 1907/2006 - REACH

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable condi-

tions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

# APPLICATION INSTRUCTIONS

## APPLICATION

Installation works to be carried out only by Sika instructed contractors for roofing.

According to the valid installation instructions for Sarnafil® flat roof waterproofing membranes.

## LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### Sika Deutschland GmbH

Roofing

Kornwestheimer Strasse 103-107

70439 Stuttgart

Tel.: +49 711/8009-0

roofing@de.sika.com

www.sika.de/dachabdichtung



### PRODUCT DATA SHEET

Sarnafil® T Pipe Flashing

September 2022, Version 01.02

020945032100001000

SarnafilTPipeFlashing-en-DE-(09-2022)-1-2.pdf

