BUILDING TRUST

SCHÖNOX® Q9 W

DECLARATION OF PERFORMANCE
No. 113090302

1	**UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:**	113090302
2	**INTENDED USE/S**	Improved fast setting cementitious adhesive for tiling EN 12004 C2FTE S1
3	**MANUFACTURER:**	Sika Deutschland CH AG & Co KG Niederlassung Rosendahl Alfred-Nobel-Str. 6 D-48720 Rosendahl
4	**SYSTEM/S OF AVCP:**	System 3, System 3 (Reaction to fire)
5a	**HARMONISED STANDARD:**	EN 12004:2007+A1:2012
	Notified body/ies:	0799, 1378

6 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Reaction to fire	Class A2fl-s1 / A2-s1, d0	System 3	EN 12004:2007 +A1:2012
Early tensile adhesion strength	≥ 0,5 N/mm²	System 3	
Initial tensile adhesion strength	≥ 1,0 N/mm²	System 3	
Tensile adhesion strength after water immersion	≥ 1,0 N/mm²	System 3	
Tensile adhesion strength after heat ageing	≥ 1,0 N/mm²	System 3	
Tensile adhesion strength after freeze/thaw cycle	≥ 1,0 N/mm²	System 3	
Dangerous substances	NPD	System 3	

7 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Jürgen Baumann
Head of Material testing and Analytics
Augsburg on 13 January 2026

. . . . . .

Volker Schwarz
Head of Material Testing
Augsburg on 13 January 2026

. . . . . .

End of information as required by Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 laying down harmonised conditions for the marketing of construction products and repealing Council Directive 89/106/EEC Text with EEA relevance

CE

13

Sika Deutschland CH AG & Co KG, Niederlassung Rosendahl, Alfred-Nobel-Str. 6, D-48720 Rosendahl

DoP No. 113090302

EN 12004:2007+A1:2012

Notified Body 0799, 1378

Improved fast setting cementitious adhesive for tiling
EN 12004 C2FTE S1

Reaction to fire	Class A2fl-s1 / A2-s1, d0
Early tensile adhesion strength	≥ 0,5 N/mm²
Initial tensile adhesion strength	≥ 1,0 N/mm²
Tensile adhesion strength after water immersion	≥ 1,0 N/mm²
Tensile adhesion strength after heat ageing	≥ 1,0 N/mm²
Tensile adhesion strength after freeze/thaw cycle	≥ 1,0 N/mm²

http://dop.sika.com

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

LEGAL NOTE

Any information provided in this Declaration of Performance ("DoP"), including any descriptions and recommendations relating to the application and end-use of any Sika products ("Products"), are given in good faith based on Sika's current knowledge and experience of the Products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. Please note that the materials, substrates and actual site conditions may vary considerably, and therefore Sika makes no warranty for merchantability or fitness for a particular purpose, and accepts no liability for the application and use of the Products, for any recommendations, or for any advice offered. Prior to using, the Product must be tested for its suitability for the intended application and purpose, and the most recent version of the Product Data Sheet must be consulted. Sika reserves the right to change the properties of its Products any time without prior notice. Any orders for Products or services provided by Sika are subject to Sika's current terms and conditions of sale.