BUILDING TRUST

SCHÖNOX® HS 10 F

DECLARATION OF PERFORMANCE
No. 121012001

1	**UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:**	121012001
2	**INTENDED USE/S**	Calcium sulfate levelling compound EN 13813 CA-C40-F10
3	**MANUFACTURER:**	Sika Deutschland CH AG & Co KG Niederlassung Rosendahl Alfred-Nobel-Str. 6 D-48720 Rosendahl
4	**SYSTEM/S OF AVCP:**	System 4, System 3 (Reaction to fire)
5a	**HARMONISED STANDARD:**	EN 13813:2002
	Notified body/ies:	1378

6 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Reaction to fire	Class A2fl-s1	System 3	EN 13813:2002
Release of corrosive substances	CA	System 4	
pH value	≥ 7	System 4	
Water vapour permeability	NPD	System 4	
Compressive strength	C40	System 4	
Flexural strength	F10	System 4	
Sound insulation	NPD	System 4	
Sound absorption	NPD	System 4	
Thermal resistance	NPD	System 4	
Chemical resistance	NPD	System 4	

7 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Tobias Benighaus
Head of Global Technology Center Rosendahl

Rosendahl on 09 February 2026

Felix Meinert
Head of R&D Mortars & Testing

Rosendahl on 09 February 2026

End of information as required by Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 laying down harmonised conditions for the marketing of construction products and repealing Council Directive 89/106/EEC Text with EEA relevance

CE

21

Sika Deutschland CH AG & Co KG, Niederlassung Rosendahl, Alfred-Nobel-Str. 6, D-48720 Rosendahl

DoP No. 121012001

EN 13813:2002

Notified Body 1378

Calcium sulfate levelling compound
EN 13813 CA-C40-F10

Reaction to fire	Class A2fl-s1
Release of corrosive substances	CA
pH value	≥ 7
Compressive strength	C40
Flexural strength	F10

http://dop.sika.com

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

LEGAL NOTE

Any information provided in this Declaration of Performance ("DoP"), including any descriptions and recommendations relating to the application and end-use of any Sika products ("Products"), are given in good faith based on Sika's current knowledge and experience of the Products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. Please note that the materials, substrates and actual site conditions may vary considerably, and therefore Sika makes no warranty for merchantability or fitness for a particular purpose, and accepts no liability for the application and use of the Products, for any recommendations, or for any advice offered. Prior to using, the Product must be tested for its suitability for the intended application and purpose, and the most recent version of the Product Data Sheet must be consulted. Sika reserves the right to change the properties of its Products any time without prior notice. Any orders for Products or services provided by Sika are subject to Sika's current terms and conditions of sale.